


NOTES :

1. ALL WELDING AND WELDING SYMBOLS SHALL CONFORM TO SABS044 PART 1 TO 5.
2. ALL STRUCTURAL USE OF STEEL TO CONFORM TO SABS 0162.
GRADE OF STEEL TO BE TO SABS 1431 GRADE 300WA.
3. ALL WELDS TO BE SEALED WELDED.
4. STEELWORK TO BE HOT DIP GALVANIZED TO SABS 1461.
5. ALL STEELWORK TO BE FABRICATED, ERECTED & LEVELED TO A TOLERANCE OF + - 1.5mm.
6. ALL BOLTS & NUTS TO CONFORM TO SABS 135, STRENGTH GRADE 4,8.
7. ALL MARKS TO BE STAMPED ONTO STEELWORK AND SHALL BE CLEARLY LEGIBLE AFTER GALVANIZING.
8. ALL HOLES TO BE 18mm DIA UNLESS OTHERWISE STATED.

[illegible]

<div> Eskom Distribution</div>		<div>PHASING DISC LABELS</div> <div>MOUNTING BRACKET DETAILS</div>			
AUTH: N. WEBBER					
DATE: 26/02/2002					
CHKD: C. Lotteri					
DATE: 25/02/2002		D-EC-1938	SET	SHEET	REVISION
DRAWN: T. Guzana				1	1
DATE: 25/02/2002					

SCALE 1:20
THIS DRAWING IS THE PROPERTY OF ESKOM