


## SEE D-DT-5016

SAP MATERIAL No.:	0172495						
SHORT DESCRIPTION:	SIGN DE - FIRST AID D6073						
TECH. DESCRIPTION:							
<p>SIGN D E * IN CASE OF FIRE PROCEDURE *</p> <p>MATERIAL : WHITE 0.6mm CHROMODEK (Z200) SCREEN PRINTED THEN CLEAR POWDER COATED TO SANS1274 OR MILD STEEL 1.2mm THICK WITH VITREOUS ENAMEL FINISHING *</p> <p>SIGN DIVIDED INTO TWO SECTIONS *</p> <p>TOP SECTION :- WORDING IN ENGLISH ONLY WITH ILLUSTRATED TREATMENT &amp; FULL FIRST AID INSTRUCTIONS *</p> <p>LETTERING BLACK ON WHITE BACKGROUND *</p> <p>MAIN HEADING - 9mm/SUB HEADING - 6mm/WRITING - 3.5mm *</p> <p>BOTTOM SECTION: - NO WATER ON FIRE LOGO *</p> <p>WORDING AS FOLLOWS :</p> <p>IN CASE OF FIRE</p> <p>DO NOT USE WATER OR FOAM</p> <p>- UNTIL SUPPLY IS ISOLATED –</p> <p>(NO WATER ON OIL FIRES) *</p> <p>LETTERING BLACK ON WHITE BACKGROUND *</p> <p>READING - 12mm/WRITING - 9mm *</p> <p>ESKOM DRAWING No. D-DT-6073 *</p>							
ITEM	:- SIGN DE - FIRST AID D6073						
MATERIAL SPECIFICATION	:- P/C CHROMODEK/VITREOUS ENAMEL						
CORROSION SPECIFICATION	:- N/A						
STANDARD SPECIFICATION	:- SANS 1186 & SANS 1247						
ESKOM SPECIFICATION	:- SCSSCAAP5 & D-DT-5016						
TEST & CERTIFICATION REQUIREMENTS :- N/A							
INSPECTION	Yes	No	ESKOM RELEASE NOTE			Yes	No
IDENTIFICATION:- INDELIBLE MANUFACTURES TRADEMARK & PART No. ON ALL ITEMS							
5	LABEL SIZES REMOVED FROM TECHNICAL DESCRIPTION.		VvZ	J.F.S.	J.SCHOLTZ	16/02/2004	
4	SDF, TECH DESC AND SPECS UPDATED		VvZ	J.F.S.	J.SCHOLTZ	15/01/2004	
3	SDF, TECH DESC AND SPECS UPDATED		VvZ	C.B.C.	A.BEKKER	10/01	
REV	REVISION DESCRIPTION		BY	CHKD	AUTH	DATE	REF. DRAWINGS
AUTH:	PHIL CROWDY	DATE:	12/96			SAP No:	
						0172495	
CHKD:	C.B. CLARK	DATE:	12/96	<b>D-DT-6073</b>		SET	SHEET
						1	1
DRAWN:	J.F.SCHOLTZ	DATE:	10/95			REV	5