



SAP MATERIAL No.:		0163528							
SHORT DESCRIPTION:		TUBE:BUSBAR;LG 12 M;OD 80 MM;ID 64 MM							
TECH. DESCRIPTION:									
TUBE: BUSBAR; LENGTH: 12 M; OUTSIDE DIAMETER: 80 MM; INSIDE DIAMETER: 64 MM; WALL THICKNESS: 8 MM; MATERIAL: AL GRADE 6061-T6; RATED CURRENT: 2.3KA ESKOM DRAWING No. D-DT-6000									
SAP MATERIAL No.:		0206318							
SHORT DESCRIPTION:		TUBE:BUSBAR;LG 12 M;OD 120 MM;ID 112 MM							
TECH. DESCRIPTION:									
TUBE: BUSBAR; LENGTH: 12 M; OUTSIDE DIAMETER: 120 MM; INSIDE DIAMETER: 112 MM; WALL THICKNESS: 4 MM; MATERIAL: AL GRADE 6061-T6; RATED CURRENT: 2.3KA ESKOM DRAWING No. D-DT-6000									
SAP MATERIAL No.:		0163535							
SHORT DESCRIPTION:		TUBE:BUSBAR;LG 10 M;OD 80 MM;ID 64 MM							
TECH. DESCRIPTION:									
TUBE: BUSBAR; LENGTH: 10 M; OUTSIDE DIAMETER: 80 MM; INSIDE DIAMETER: 64 MM; WALL THICKNESS: 8 MM; MATERIAL: AL GRADE 6061-T6; RATED CURRENT: 2.3KA ESKOM DRAWING No. D-DT-6000									
ITEM		:- TUBE AL 12m L D6000							
MATERIAL SPECIFICATION		:- 240-122922610							
CORROSION SPECIFICATION		:- 240-122922610							
STANDARD SPECIFICATION		:- 240-122922610							
ESKOM SPECIFICATION		:- 240-122922610							
TEST & CERTIFICATION REQUIREMENTS		:- 240-122922610							
INSPECTION		Yes	No	ESKOM RELEASE NOTE		Yes	No		
IDENTIFICATION:- INDELIBLE MANUFACTURES TRADEMARK & PART No. ON ALL ITEMS									
5	TUBE:BUSBAR;LG 10 M;OD 120 MM;ID 112 MM ADDED. SAP and SPECIFICATIONS UPDATED			JS	Athelene Gouws	Theunus Marais	05/10/2020		
4	TUBE 120mm OD x 4 mm W THK ADDED.			VvZ	JFS	J.F.SCOLTZ	19/09/2003		
3	D-DT-6000 SHT 2 REPOSITIONED FROM D-DT-6001. SFD CHANGED & RATED CURRENT ADDED			VvZ	C.B.C.	A.BEKKER	10/01		
2	VARIOUS AMMENDMENTS MADE			P.A.V.	C.B.C.	P.CROWDY	05/00		
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE		
AUTH:		PHIL CROWDY	DATE:	12/96	 <b>D-DT-6000</b>		SAP No:		
CHKD:		C.B. CLARK	DATE:	12/96			0163528 0206318		0163535
DRAWN:		J.F.SCHOLTZ	DATE:	10/96			SET	SHEET	REV
							2	1	5

## SPEC SHEET

SAP MATERIAL No.:				0501194					
SHORT DESCRIPTION:				TUBE:BUSBAR;LG 10 M;OD 120 MM;ID 112 MM					
TECH. DESCRIPTION:									
TUBE: BUSBAR; LENGTH: 10 M; OUTSIDE DIAMETER: 120 MM; INSIDE DIAMETER: 112 MM; WALL THICKNESS: 4 MM; MATERIAL: AL GRADE 6061-T6; RATED CURRENT: 2.3KA ESKOM DRAWING No. D-DT-6000									
5	TUBE:BUSBAR;LG 10 M;OD 120 MM;ID 112 MM ADDED. SAP and SPECIFICATIONS UPDATED			JS	Athelene Gouws	Theunus Marais	05/10/2020		
4	TUBE 120mm OD x 4 mm W THK ADDED.			VvZ	JFS	J.F.SCOLTZ	19/09/2003		
3	D-DT-6000 SHT 2 REPOSITIONED FROM D-DT-6001. SFD CHANGED & RATED CURRENT ADDED			VvZ	C.B.C.	A.BEKKER	10/01		
2	VARIOUS AMMENDMENTS MADE			P.A.V.	C.B.C.	P.CROWDY	05/00		
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DRAWINGS	
AUTH:	PHIL CROWDY	DATE:	12/96	SCALE NTS				SAP No:	
CHKD:	C.B. CLARK	DATE:	12/96	CAD REF:				0501194	
DRAWN:	J.F.SCHOLTZ	DATE:	10/96	SERIES 6000		SET		SHEET	REV
				FILE No: 6000		2		2	5
D-DT-6000									