

SAP MATERIAL No.:	0402629
-------------------	---------

SHORT DESCRIPTION:	CLAMP,SUSP PIVOTED 25.0-40.0 D7009
--------------------	------------------------------------


TECH. DESCRIPTION:	<p>PIVOTED SUSPENSION CLAMP * MALLEABLE CAST IRON *</p> <p>HOT DIPPED GALVANISED OR HEAT TREATED DIE CAST ALUMINIUM ALLOY *</p> <p>CLEVIS DIMENSIONS TO SANS 60471 DESIGNATION 16L *</p> <p>NOMINAL COUPLING LENGTH 100mm *</p> <p>SUPPLIED COMPLETE:</p> <p>1 x M16 CLEVIS BOLT ASSEMBLY (D-DT-7043),</p> <p>4 x M12 SPRING WASHERS (D-DT-3014), 4 x M12 HEX. BOLTS (D-DT-3173) *</p> <p>2 x M12 U-BOLTS (SUITABLE LENGTH FOR ALL CONDUCTOR RANGES)</p> <p>CONDUCTOR RANGE :- (INCLUDING PREFORMED ARMOR RODS)</p> <p>25.0mm TO 40mm DIAMETER *</p> <p>CAN BE USED WITH WOLF, CHICADEE, BEAR, KINGBIRD, CENTIPEDE *</p> <p>MINIMUM FAILING LOAD 70kN *</p> <p>ESKOM DRAWING No. D-DT-7009 *</p>
--------------------	---

ITEM	:-	CLAMP,SUSP PIVOTED 25.0-40.0
MATERIAL SPECIFICATION	:-	SANS 991, SANS 992, BS EN 1562
CORROSION SPECIFICATION	:-	SANS 121
STANDARD SPECIFICATION	:-	SANS 61284, SANS 60471
ESKOM SPECIFICATION	:-	TRMSCAAH2, DSP 34-1667
TEST & CERTIFICATION REQUIREMENTS	:-	TYPE TEST ACCORDING TO SANS 61284 AND DSP 34-1667

INSPECTION	Yes	No	ESKOM RELEASE NOTE	Yes	No
------------	-----	----	--------------------	-----	----

IDENTIFICATION:- INDELIBLE MANUFACTURES TRADEMARK & PART No. ON ALL ITEMS

8	TURN REMOVED FROM TECH. DESCRIPTION	P.A.T.	B. HILL	B. HILL	01.07.2015	
7	BULL COND REMOVED FROM USE OF SUSPENSION CLAMP	P.A.T.	S. MASHABA	B.BRANFIELD	20.04.2010	
6	MATERIAL, STD. ESKOM SPECS CHANGED AND DRG. NO.'S ADDED	P.A.T.	S. MASHABA	S. MASHABA	03.08.2009	

REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DWGS
AUTH:	P. CROWDY	DATE:	26.03.1998	SCALE	 D-DT-7009			SAP No:
CHKD:	D. PILLAY	DATE:	26.03.1998	NTS				0402629
DRAWN:	GC P.A. VERMAAK	DATE:	08.11.1997 01.03.1998	CAD REF:				SET
				SERIES 7000				SHEET
				FILE No:				REV
				7009				1
								1
								8