



Request for Quote

Printed: 07.06.2022

Page:

1 of 3

Number:

6000334998

Date:

07.06.2022

VAT REG NO: 4740101508

ESKOM HOLDINGS GENERATION

eskom holdings generation Ltd

P O Box 2634

johannesburg

2157

RFQ Collective number

LPMED0028G

Contact person

MAHLATJIE TISETSO MOLABE

Your person responsible/Your reference

Please deliver to:

Medupi Power Station.

Grootegeluk-Onverwacht Road

Ellisras.

0555

Your vendor number with us

11070302

Quotation deadl.: 20.06.2022

Medupi Power Station CX

Procurement

Private Bag X7502 Onverwacht 0557 SA

Tel 0118008111 Fax

Item	Material	Description	Deliv. date
RFQ quantity	Unit		
00010	0574050	DETECTOR RT:PT100;200 DEG C;80 MM;3	
10	each		Day 31.08.2022
DETECTOR, RESISTANCE TEMPERATURE: TYPE: PT100; TEMPERATURE RATING: 200 DEG C; RESISTANCE: 100 OHM AT 0 DEG C; SHEATH LENGTH: 80 MM; WIRE: 3; SHEATH SIZE: 80 MM; SHEATH MATERIAL: SS GR 316; PROCESS CONNECTION: 1/2 IN-NPT SS COMPRESSION FITTING; HEAD: YES; SHEATH DIAMETER: 6 MM; NUMBER OF SENSORS: SINGLE; MANUF P/N: G RX96-.3-80-FM-100-C-4F4S; HEAD MATERIAL: DIE CAST ALLOY; FOR USE ON SSC WATER TEMP MEASUREMENT			
00020	0624482	DETECTOR RT:PT100;-200 TO 600 DEG C;4	
236	each		Day 29.09.2022
DETECTOR, RESISTANCE TEMPERATURE: TYPE: PT100; TEMPERATURE RATING: -200 TO 600 DEG C; RESISTANCE: 100 OHM AT 0 DEG C; SHEATH LENGTH: 410 MM; WIRE: 4; SHEATH MATERIAL: SS GR 316L; PROCESS CONNECTION: CERAMIC TERMINAL BLOCK; TOLERANCE: NO; SHEATH DIAMETER: 3 MM; NUMBER OF SENSORS: SINGLE; MANUF P/N: TPR100-A1CC000; REFERENCE NO: EA0A2014180			
00030	0624480	DETECTOR RT:PT100;-200 TO 600 DEG C;4	
303	each		Day 31.10.2022
DETECTOR, RESISTANCE TEMPERATURE: TYPE: PT100; TEMPERATURE RATING: -200 TO 600 DEG C; RESISTANCE: 100 OHM AT 0 DEG C; SHEATH LENGTH: 510 MM; WIRE: 4; SHEATH MATERIAL: SS GR 316L; PROCESS CONNECTION: CERAMIC TERMINAL BLOCK; TOLERANCE: NO; SHEATH DIAMETER: 3 MM; NUMBER OF SENSORS: SINGLE; REFERENCE NO: EA065614180; SUPPL P/N: TPR100-A1CC000			
00040	0679082	DETECTOR RT:PT100;200-600 DEG C;1585 MM	
13	each		Day 31.08.2022
Manufacturer part number Manuf. Manuf. pl. Rev. 1. TRP100-AXX2CC000; H6175514180			
DETECTOR, RESISTANCE TEMPERATURE: TYPE: PT100; TEMPERATURE RATING: 200-600 DEG C; RESISTANCE: 100 OHM AT 0 DEG C; SHEATH LENGTH: 1585 MM; WIRE: 4; PROCESS CONNECTION: CERAMIC TERMINAL BLOCK; SHEATH DIAMETER: 6 MM; NUMBER OF SENSORS: SINGLE; RTD SENSOR ENDRESS AND HAUSER PT100; -200 TO 600 DEGREES CELSIUS; PART NUMBER: TPR100-AXX2CC000; PART NUMBER TPR100-AXX2CC000; LG 1585MM			
00050	0624478	DETECTOR RT:PT100;-50 TO 400 DEG C;4	
20	each		Day 10.11.2022
DETECTOR, RESISTANCE TEMPERATURE: TYPE: PT100; TEMPERATURE RATING: -50 TO 400 DEG C; RESISTANCE: 100 OHM AT 0 DEG C; SHEATH LENGTH: 1.435 M; WIRE: 4;			



Request for Quote

Printed: 07.06.2022

Page:

3 of 3

Number:

6000334998

Date:

07.06.2022

VAT REG NO: 4740101508

Item	Material	Description	Deliv. date
RFQ quantity	Unit		
SHEATH MATERIAL: SS GR 316L; PROCESS CONNECTION: CERAMIC TERMINAL BLOCK; TOLERANCE: NO; SHEATH DIAMETER: 6 MM; NUMBER OF SENSORS: SINGLE; DRAWING NO: F314B14180 REV 0; SUPPL P/N: TPR100-A2C7OEO			
00060	0618289	DETECTOR:COMPACT FLAME MONITOR	
21	each		Day 27.07.2022
DETECTOR: TYPE: COMPACT FLAME MONITOR; RATING: 24 VDC 5 W 4-20 MA; MOUNTING: G1-1/4 IN; SPECIFICATION: EN 60529; REFERENCE NO: 1179631; SUPPL P/N: 1117787; D-LX200-IG-20/MP; APPLICATION: COAL SENSOR; WITH UV PHOTO-DIOD (190NM TO 520NM); PROTECTION CLASS: IP65; TEMPERATURE RANGE: -40 TO 85 DEG C			
00070	0618290	DETECTOR:COMPACT FLAME MONITOR	
20	each		Day 31.08.2022
DETECTOR: TYPE: COMPACT FLAME MONITOR; RATING: 24 VDC 5 W 4-20 MA; MOUNTING: G2-3/4 IN-BSPP; SPECIFICATION: EN 60529; REFERENCE NO: 1179407; SUPPL P/N: 1117791; D-LX720 UA-20/MP; APPLICATION: OIL HEAT SENSOR; WITH IR PHOTO-DIOD (780NM TO 1800NM); PROTECTION CLASS: IP65; TEMPERATURE RANGE: -40 TO 85 DEG C; PURGE CONNECTION ON THE SIDE			
00080	0574399	MONITOR VIDEO:LCD;24 IN;220-240VAC 50HZ	
5	each		Day 30.08.2022
MONITOR, VIDEO: TYPE: LCD; SIZE: 24 IN; POWER SOURCE: 220-240VAC 50HZ; MANUF P/N: E52L0502850; EA241 WM-BK (G); TN TFT; ALSPA HMI 724 UNIT FOR WORKSTATION, MULTISYNC			
00090	0648040	MONITOR:IR FLAME;0-20 MA;24 VDC	
15	each		Day 17.08.2022
MONITOR: TYPE: IR FLAME; RANGE: 0-20 MA; POWER SOURCE: 24 VDC; SUPPL P/N: D-LX 200 1G 20 MP; IP 65; SPECTRAL SENSITIVITY OF 2=780MM TO 1800MM			
00100	0580209	DETECTOR RT:RTD-PT100;0-100 DEG C;4;NO	
20	each		Day 28.07.2022
DETECTOR, RESISTANCE TEMPERATURE: TYPE: RTD-PT100; TEMPERATURE RATING: 0-100 DEG C; RESISTANCE: 300 OHM; WIRE: 4; HEAD: NO; TOLERANCE: 0.075 PCT; MANUF P/N: TMT122-A41BBA; REFERENCE NO: E9029E041C1			