



Request for Quote

Printed: 16.06.2022

Page:

1 of 3

Number:

6000336264

Date:

16.06.2022

VAT REG NO: 4740101508

ESKOM HOLDINGS GENERATION

eskom holdings generation Ltd

P O Box 2634

johannesburg

2157

RFQ Collective number

Contact person

CYNTHIA ZANELE NDABA

Your person responsible/Your reference

Please deliver to:

Kendal Power Station.

(Near Ogies, on Jhb/Witbank Road)

Kendal Power Station, Main Store

Witbank

1035

Your vendor number with us

11070302

Quotation deadl.: 30.06.2022

Delivery date: Day 11.07.2022

ERROR: No office address maintained

SA

Tel 0116294537 Fax

Item	Material	Description	Deliv. date
RFQ quantity	Unit		
00010		HOSE FIRE:ID 65MM MM;LG 30M M;NONE;RED	
30	each	Your material number STM-036634 HOSE, FIRE: INSIDE DIAMETER: 65MM MM; LENGTH: 30M M; CONNECTION: NONE; MATERIAL: RUBBER HOSE; TEST PRESSURE: 400 KPA; COLOR: RED; TYPE: ESCHBACH; SPECIFICATION: SANS 1086; 2.1MM WALL THICKNESS; LAYFLAT DELIVERY; CONNECTION NONE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	
00020		COUPLING PIPE:30M X 45 MM MM;FPT;MI GALV	
30	each	Your material number STM-036636 COUPLING, PIPE: SIZE: 30M X 45 MM MM; CONNECTION: FPT; MATERIAL: MI GALV; RATING: BIC; SPECIFICATION: SABS 763; SCHEDULE: 45MM; GRADE: FIRE HOSE; STYLE: BIC COUPLING; COLOR CODING: RED; MEDIA FOR WHICH DESIGNED: PF PIPE; 33MM LONG; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	
00030		COUPLER HOSE:LAYFLAT HOSES;30M MM;N/A	
20	each	Your material number STM-036639 COUPLER, HOSE: TYPE: LAYFLAT HOSES; SIZE: 30M MM; CONNECTION: 2 INCH HOSES FITTED WRE; MATERIAL: N/A; SPECIFICATION: 3S INCH HOSES MUST BE FITTED WITH WRE; LAYFLAT HOSES FITTED WITH WRE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	
00040		POSITIONER VLV:G-FORCE;2.5 BICM BAR	
6	each	Your material number STM-036644 POSITIONER, VALVE: TYPE: G-FORCE; SUPPLY PRESSURE: 2.5 BICM BAR; INPUT: 7 BAR; FABRIC FILTER PLANT CELL PULSE AIR CONTROL VALVE OUTLET ISOLATING VALVE ELECTRICAL CONTROL SIGNAL 4-20MA TYPE KINETROL (AP) MATERIAL TEST CERTIFICATE TO BE SUPPLIED AT DELIVERY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	
00050		FOAM:FIRE FIGHTING;CAN PLASTIC PRO/PAK	
4	each	Your material number STM-036647 FOAM: TYPE: FIRE FIGHTING; PACKAGE TYPE: CAN PLASTIC PRO/PAK;	



Request for Quote

Printed: 16.06.2022

Page: 3 of 3
Number: 6000336264
Date: 16.06.2022

VAT REG NO: 4740101508

Item	Material	Description	Deliv. date
RFQ quantity	Unit		

CONTAINER CAPACITY: 2.5' L; FILM FORMING; SUPPLIER NOTE, THE ITEM WILL NOT BE ACCEPTED WITHOUT A MATERIAL SAFETY DATA SHEET WITH EVERY DELIVERY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).