

<b>Vehicle Job Description:</b>	Required for carrying Goods, equipment and	
<b>T11</b>	<b>Annexure A3</b>	<b>Tendering S</b>
<b>Vehicle Type Required:</b>	<b>Heavy Truck 6x6 26000 GCM (Single Wheel application)</b>	<b>Comply</b>
AIR CONDITIONER (Factory Warranty)	To be Standard	
RADIO/CD PRICE FITTED (IF NOT STD)	To be Standard	
Seat Belts: SABS APPROVED	To be Standard	
DRIVER AND PASSENGER SEATBELT REMINDER INDICATOR/ALARM	To be Standard	
ABS BRAKES	To be Standard	
POWER STEERING	To be Standard	
DAY RUN LIGHTS INSTALLED	To be Standard	
TWO EMERGENCY TRIANGLES	To be Standard	
IMMOBILISER (Factory Warranty)	To be Standard	
ALARM (Factory Warranty)	To be Standard	
WHEEL BASE EXTENSION IF NEEDED (PRICE FITTED IF NOT STD) FROM 4525mm 6000MM	To be Standard	
PTO Suitable for a 21Tm crane (PRICE FITTED IF NOT STD)	To be Standard	
ENGINE PROTECTION DEVICE	To be Standard	
TRAILER BRAKE CONTROL	To be Standard	
AIR CHARGE LINE TO THE FRONT	To be Standard	
REVERSE ALARM/BEEPER	To be Standard	
FITTED TOWING/RECOVERY FACILITY ON FRONT	To be Standard	
VEHICLE CONFIGURATION :	Heavy Truck 6x6 42000 GCM <b>(Single Wheel application)</b>	
TRACTION:	6x6	
Diesel Powered (Normally aspirated or Turbo)	YES	
Power Rating - Kw	272Kw	
Torque Rating - NM	1500Nm	
Permissible Front axle rating " Max."	8000kg	
Permissible Rear axle rating " Max."	26000kg	
D/T Rating "Min."	42000Kg	
Wheel base " Max."	4525mm	
Chassis to facilitate the fitting of 22Tm hydraulic crane	YES	
Fully synchromesh Gearbox	YES	
Power assisted Steering	YES	
Seat Belts: SABS approved	YES	
Tyres (Size) 1400R20 Steel radial Tyres (Michelin XZL) <b>(up to 80% off road usage)</b> Compatible diff ratio	YES	
Number of gears, manual	YES	
Mud-flaps: Factory fitted	YES	
WARRANTY PERIOD: MONTHS/DISTANCE	Specify	
CARBON DIOXIDE (CO <sub>2</sub> ) EMISSION: g/km	Specify	
Acceptance / Acceptance		
Name of Evaluator :		Signature :

Name of Verifier

Signature :

Any proposed deviations from this specification shall be listed below with reasons for the deviation(s). In addition

Technical Evaluation Criteria	100
Fully completed questionnaire in Annexure A3 confirming the compliance and non-compliance to the technical specification as well as prove (brochures) for verification of compliance.	50
Original Equipment manufacturer (OEM) or register dealer	20
Proof of 12 (twelve) month warranty certificate from the Original Equipment manufacturer (OEM)	20
Proof of after sales service and repairs (OEM Service Level Agreement)	10

passengers of 26000 kg GVM and above on all types of road surfaces with up to 40%

Service Provider to complete

Eskom technical team to complete

	Compliance	Non-compliance
Provide reason for Comply or non-compliance		

Eskom technical evaluation comments	
1	
2	
3	
4	
5	
6	
7	
8	
9	
10	
11	
12	
13	
14	
15	
16	
17	
18	
19	
20	
21	
22	
23	
24	
25	
26	
27	
28	
29	
30	
31	
32	
33	
34	
35	
36	
37	
38	
39	
40	
41	
42	
43	
44	
45	
46	
47	
48	
49	
50	
51	
52	
53	
54	
55	
56	
57	
58	
59	
60	
61	
62	
63	
64	
65	
66	
67	
68	
69	
70	
71	
72	
73	
74	
75	
76	
77	
78	
79	
80	
81	
82	
83	
84	
85	
86	
87	
88	
89	
90	
91	
92	
93	
94	
95	
96	
97	
98	
99	
100	

[illegible][illegible]

on, evidence shall be provided that the proposed deviation will at least be more cost-	

Permitted Ancillaries
23 Tm & 21m Horizontal & 650Kg
32 Tm & 20m Horizontal & 880Kg
Hour meter
Inter lock hand brake system
28m Live line Aerial platform
30m Non insulated Telescopic Aerial platform
HHH DTH Drill and 900 CFM compressor (HHH DTH OBC)
Tail lift 3 Ton capacity
PTO
Flat Bed Drop side
Cargo van body
Crew cab
Ladder Rack
"H" Frame
Tool Boxes
Stainless steel Water Tank
Working Lights
Amber Revolving Light
Tow bar
Under run bumper fixed or energy absorbing type
Winch type spare wheel carrier
Wheel Flaps: SABS 1496 specification (Jan 1999)
Yellow reflective tape that must be fitted (Road traffic Act and Regulations No. 192A)
Homologation of load body according to (Road traffic Act and Regulations No. 192A)