

18V Battery Driven Grease Gun with 2 batteries charger and case
PLEASE COMPLETE SCHEDULE B

Complete Schedule B: Do not Tick or Cross, Handwrite on Schedule B column.

Item	Description	Units	Schedule A	Schedule B
1	FUNCTIONALITY			
1.2	Voltage	V	18V	
1.3	Battery Pack Capacity	Ah	1,5	
1.4	Battery charger	V,Hz	220-240V, 50-60Hz	
1.5	Battery Charger time(max)	Min	90	
1.6	Case dimensions (l x h x w)	Mm	50 x 110 x 370	
1.7	Operating temperature range	Deg Cel	-20 to 50	
1.8	Product weight	Kg	3	
1.9	Hose length	Mm	900	
1.10	Maximum pressure	MPa	40	
1.11	Grease output 70 bar (1000 psi) – Low speed	ml/min	100	
1.12	Grease output 70 bar (1000 psi) – Low speed	ml/min	160	
2	DOCUMENTATION (to be submitted with tender)			
2.1	Approved manufacturer catalogue with user manual.	1 Set submitted	Yes	
3	PRODUCT ACCEPTANCE REPORTS			
3.1	Proof that the product is approved by SANAS accredited body like SABS	Signed test schedule submitted	Yes	