




SPEC SHEET											
SAP MATERIAL No.:		0187151									
SHORT DESCRIPTION:		PADLOCK, ST LV MASTER, G OU D6050									
TECH. DESCRIPTION:											
WEATHER PROOF PADLOCK * FOR GAUTENG OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * ORANGE RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: THREE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *											
SAP MATERIAL No.:		0187152									
SHORT DESCRIPTION:		PADLOCK, ST LV MASTER KZN OU D6050									
TECH. DESCRIPTION:											
WEATHER PROOF PADLOCK * FOR KWAZULU NATAL OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * ORANGE RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: THREE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *											
SAP MATERIAL No.:		0187153									
SHORT DESCRIPTION:		PADLOCK, ST LV MASTER WC OU D6050									
TECH. DESCRIPTION:											
WEATHER PROOF PADLOCK * FOR WESTERN CAPE OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * ORANGE RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: THREE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *											
ITEM		:- PADLOCK & PADLOCK KEYS									
MATERIAL SPECIFICATION		:- NYLON, LAMINATED STEEL									
CORROSION SPECIFICATION		:- DSP 34 1488									
STANDARD SPECIFICATION		:- SANS 1533									
ESKOM SPECIFICATION		:- DSP 34 1488;									
TEST & CERTIFICATION REQUIREMENTS		:- DSP 34 1488									
INSPECTION		Yes	No	ESKOM RELEASE NOTE				Yes	No		
IDENTIFICATION:- INDELIBLE MANUFACTURERS TRADEMARK & PART No. ON ALL ITEMS											
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED			P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013				
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.			VvZ	VvZ	C.D.SMITH	12/08/2004				
1	ALL PADLOCKS REPLACED AND KEYS ADDED			VvZ	VvZ	C.D.SMITH	6/5/02				
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DRAWINGS			
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE NTS		 D-DT-6050		SAP No:			
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:				0187151		0187153	
				SERIES 6000				SET		SHEET	
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No: 6050				REV			
								45	1	3	


SPEC SHEET

SAP MATERIAL No.:		0573490								
SHORT DESCRIPTION:		PADLOCK:ST LV MASTER; ORG; NC OU								
TECH. DESCRIPTION:										
PADLOCK: TYPE: ST GENERAL MASTER; ORG; NC OU; SHACKLE DIAMETER: 6 MM; CASE SIZE: WD 40 X HT 38 X THK 20 MM; HORIZONTAL CLEARANCE: 20 MM; VERTICAL CLEARANCE: 30 MM; MATERIAL: LAMINATED STEEL WITH QUALITY ZINC PLATING; WEATHER PROOF PADLOCK; FOR NORTHERN CAPE OPERATING UNIT ONLY; ORANGE RUBBER CASING; LOCKED BY DUAL STAINLESS STEEL BALL MECHANISM; NICKEL COATED 304 GRADE STAINLESS STEEL DIN 17224; MECHANISM: THREE PIN TUMBLER CYLINDER TYPE WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN; PIN SPRINGS: PHOSPHER BRONZE; ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0187154								
SHORT DESCRIPTION:		PADLOCK, ST LV MASTER EC OU D6050								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR EASTERN CAPE OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * ORANGE RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: THREE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0187155								
SHORT DESCRIPTION:		PADLOCK, ST LV MASTER L OU D6050								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR LIMPOPO OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * ORANGE RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: THREE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *										
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED			P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013			
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.			VvZ	VvZ	C.D.SMITH	12/08/2004			
1	ALL PADLOCKS REPLACED AND KEYS ADDED			VvZ	VvZ	C.D.SMITH	6/5/02			
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DRAWINGS		
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE NTS		 D-DT-6050		SAP No:		
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:				0573490		0187155
				SERIES 6000				SET		
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:				45	2	3
				6050						


SPEC SHEET

SAP MATERIAL No.:		0187156								
SHORT DESCRIPTION:		PADLOCK, ST LV MASTER MP OU D6050								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR MPUMALANGA OPERATING UNIT ONLY *										
PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING *										
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *										
ORANGE RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *										
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *										
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *										
MECHANISM: THREE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *										
ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0187157								
SHORT DESCRIPTION:		PADLOCK, ST LV MASTER FS OU D6050								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR FREE STATE OPERATING UNIT ONLY *										
PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING *										
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *										
ORANGE RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *										
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *										
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *										
MECHANISM: THREE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *										
ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0573709								
SHORT DESCRIPTION:		PADLOCK:ST LV MASTER; ORG; NW OU								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR NORTHWEST OPERATING UNIT ONLY *										
PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING *										
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *										
ORANGE RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *										
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *										
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *										
MECHANISM: THREE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *										
ESKOM DRAWING No. D-DT-6050 *										
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED			P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013			
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.			VvZ	VvZ	C.D.SMITH	12/08/2004			
1	ALL PADLOCKS REPLACED AND KEYS ADDED			VvZ	VvZ	C.D.SMITH	6/5/02			
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DRAWINGS		
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE NTS				SAP No:		
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:				0187156		0573709
				SERIES 6000				SET		
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No: 6050		D-DT-6050		45	3	3


SPEC SHEET

SAP MATERIAL No.:		0187158						
SHORT DESCRIPTION:		PADLOCK, ST PROH MASTER G OU D6050						
TECH. DESCRIPTION:								
WEATHER PROOF PADLOCK * FOR GAUTENG OPERATING UNIT ONLY *								
PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING *								
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *								
GREEN RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *								
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *								
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *								
MECHANISM: FOUR PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *								
ESKOM DRAWING No. D-DT-6050 *								
SAP MATERIAL No.:		0187159						
SHORT DESCRIPTION:		PADLOCK, ST PROH MASTER KZN OU D6050						
TECH. DESCRIPTION:								
WEATHER PROOF PADLOCK * FOR KWAZULU NATAL OPERATING UNIT ONLY *								
PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING *								
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *								
GREEN RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *								
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *								
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *								
MECHANISM: FOUR PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *								
ESKOM DRAWING No. D-DT-6050 *								
SAP MATERIAL No.:		0187160						
SHORT DESCRIPTION:		PADLOCK, ST PROH MASTER WC OU D6050						
TECH. DESCRIPTION:								
WEATHER PROOF PADLOCK * FOR WESTERN CAPE OPERATING UNIT ONLY *								
PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING *								
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *								
GREEN RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *								
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *								
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *								
MECHANISM: FOUR PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *								
ESKOM DRAWING No. D-DT-6050 *								
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED			P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013	
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.			VvZ	VvZ	C.D.SMITH	12/08/2004	
1	ALL PADLOCKS REPLACED AND KEYS ADDED			VvZ	VvZ	C.D.SMITH	6/5/02	
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DRAWINGS
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE		<div></div> <div>D-DT-6050</div>		
				NTS				
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:				
				SERIES 6000				
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:		<div>45</div> <div>4</div> <div>3</div>		
				6050				
						SAP No: 0187158 0187159 0187160		
						SET	SHEET	REV

SPEC SHEET

SAP MATERIAL No.:		0573491									
SHORT DESCRIPTION:		PADLOCK:ST PROH MASTER; GRN; NC OU									
TECH. DESCRIPTION:											
PADLOCK: TYPE: ST PROH MASTER; GRN; NC OU; SHACKLE DIAMETER: 6 MM; CASE SIZE: WD 40 X HT 38 X THK 20 MM; HORIZONTAL CLEARANCE: 20 MM; VERTICAL CLEARANCE: 30 MM; MATERIAL: LAMINATED STEEL WITH QUALITY ZINC PLATING; WEATHER PROOF PADLOCK; FOR NORTHERN CAPE OPERATING UNIT ONLY: GREEN RUBBER CASING; LOCKED BY DUAL STAINLESS STEEL BALL MECHANISM; NICKEL COATED 304 GRADE STAINLESS STEEL DIN 17224; MECHANISM: THREE PIN TUMBLER CYLINDER TYPE WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN; PIN SPRINGS: PHOSPHER BRONZE; ESKOM DRAWING No. D-DT-6050 *											
SAP MATERIAL No.:		0187161									
SHORT DESCRIPTION:		PADLOCK, ST PROH MASTER EC OU D6050									
TECH. DESCRIPTION:											
WEATHER PROOF PADLOCK * FOR EASTERN CAPE OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * GREEN RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: FOUR PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *											
SAP MATERIAL No.:		0187162									
SHORT DESCRIPTION:		PADLOCK, ST PROH MASTER L OU D6050									
TECH. DESCRIPTION:											
WEATHER PROOF PADLOCK * FOR LIMPOPO OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * GREEN RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: FOUR PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *											
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED			P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013				
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.			VvZ	VvZ	C.D.SMITH	12/08/2004				
1	ALL PADLOCKS REPLACED AND KEYS ADDED			VvZ	VvZ	C.D.SMITH	6/5/02				
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DRAWINGS			
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE NTS		 D-DT-6050		SAP No: 0573491		0187162	
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:				SET	SHEET		REV
				SERIES 6000				45	5		3
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No: 6050							

SPEC SHEET

SAP MATERIAL No.:		0187163						
SHORT DESCRIPTION:		PADLOCK, ST PROH MASTER MP OU D6050						
TECH. DESCRIPTION:								
WEATHER PROOF PADLOCK * FOR MPUMALANGA OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * GREEN RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: FOUR PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *								
SAP MATERIAL No.:		0187164						
SHORT DESCRIPTION:		PADLOCK, ST PROH MASTER FS OU D6050						
TECH. DESCRIPTION:								
WEATHER PROOF PADLOCK * FOR FREE STATE OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * GREEN RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: FOUR PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *								
SAP MATERIAL No.:		0573710						
SHORT DESCRIPTION:		PADLOCK:ST PROH MASTER; GRN; NW OU						
TECH. DESCRIPTION:								
WEATHER PROOF PADLOCK * FOR NORTH-WEST OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * GREEN RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: FOUR PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *								
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED		P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013		
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.		VvZ	VvZ	C.D.SMITH	12/08/2004		
1	ALL PADLOCKS REPLACED AND KEYS ADDED		VvZ	VvZ	C.D.SMITH	6/5/02		
REV	REVISION DESCRIPTION		BY	CHKD	AUTH	DATE	REF. DRAWINGS	
AUTH:	PHIL CROWDY	DATE:	03/98			SAP No:		
CHKD:	C.B. CLARK	DATE:	03/98			0187163		0573710
						0187164		
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	D-DT-6050		SET	SHEET	REV
						45	6	3


SPEC SHEET

SAP MATERIAL No.:		0187165					
SHORT DESCRIPTION:		PADLOCK, ST OPER MASTER G OU D6050					
TECH. DESCRIPTION:							
WEATHER PROOF PADLOCK * FOR GAUTENG OPERATING UNIT ONLY *							
PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING *							
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *							
YELLOW RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *							
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *							
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *							
MECHANISM: FIVE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *							
ESKOM DRAWING No. D-DT-6050 *							


SAP MATERIAL No.:		0187166					
SHORT DESCRIPTION:		PADLOCK, ST OPER MASTER KZN OU D6050					
TECH. DESCRIPTION:							
WEATHER PROOF PADLOCK * FOR KWAZULU NATAL OPERATING UNIT ONLY *							
PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING *							
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *							
YELLOW RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *							
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *							
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *							
MECHANISM: FIVE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *							
ESKOM DRAWING No. D-DT-6050 *							

SAP MATERIAL No.:		0187167					
SHORT DESCRIPTION:		PADLOCK, ST OPER MASTER WC OU D6050					
TECH. DESCRIPTION:							
WEATHER PROOF PADLOCK * FOR WESTERN CAPE OPERATING UNIT ONLY *							
PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING *							
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *							
YELLOW RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *							
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *							
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *							
MECHANISM: FIVE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *							
ESKOM DRAWING No. D-DT-6050 *							


3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED		P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013	
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.		VvZ	VvZ	C.D.SMITH	12/08/2004	
1	ALL PADLOCKS REPLACED AND KEYS ADDED		VvZ	VvZ	C.D.SMITH	6/5/02	
REV	REVISION DESCRIPTION		BY	CHKD	AUTH	DATE	REF. DRAWINGS

AUTH:	PHIL CROWDY	DATE:	03/98	SCALE		SAP No:		
				NTS		0187165	0187167	
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:		0187166		
				SERIES 6000		SET	SHEET	REV
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:	D-DT-6050			
				6050		45	7	3


SPEC SHEET

SAP MATERIAL No.:		0573492								
SHORT DESCRIPTION:		PADLOCK:ST OPER MASTER; YEL; NC OU								
TECH. DESCRIPTION:										
PADLOCK: TYPE: ST OPER MASTER; YEL; NC OU; SHACKLE DIAMETER: 6 MM; CASE SIZE: WD 40 X HT 38 X THK 20 MM; HORIZONTAL CLEARANCE: 20 MM; VERTICAL CLEARANCE: 30 MM; MATERIAL: LAMINATED STEEL WITH QUALITY ZINC PLATING; WEATHER PROOF PADLOCK; FOR NORTHERN CAPE OPERATING UNIT ONLY: YELLOW RUBBER CASING; LOCKED BY DUAL STAINLESS STEEL BALL MECHANISM; NICKEL COATED 304 GRADE STAINLESS STEEL DIN 17224; MECHANISM: THREE PIN TUMBLER CYLINDER TYPE WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN; PIN SPRINGS: PHOSPHER BRONZE; ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0187168								
SHORT DESCRIPTION:		PADLOCK, ST OPER MASTER EC OU D6050								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR EASTERN CAPE OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * YELLOW RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: FIVE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0187169								
SHORT DESCRIPTION:		PADLOCK, ST OPER MASTER L OU D6050								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR LIMPOPO OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * YELLOW RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: FIVE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *										
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED			P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013			
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.			VvZ	VvZ	C.D.SMITH	12/08/2004			
1	ALL PADLOCKS REPLACED AND KEYS ADDED			VvZ	VvZ	C.D.SMITH	6/5/02			
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DRAWINGS		
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE NTS				SAP No:		
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:				0573492	0187168	
				SERIES 6000				SET		SHEET
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No: 6050		D-DT-6050		45	8	3


SPEC SHEET

SAP MATERIAL No.:	0187170					
SHORT DESCRIPTION:	PADLOCK, ST OPER MASTER MPUMALANGA D6050					
TECH. DESCRIPTION:						
WEATHER PROOF PADLOCK * FOR MPUMALANGA OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * YELLOW RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: FIVE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *						
SAP MATERIAL No.:	0187171					
SHORT DESCRIPTION:	PADLOCK, ST OPER MASTER FS OU D6050					
TECH. DESCRIPTION:						
WEATHER PROOF PADLOCK * FOR FREE STATE OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * YELLOW RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: FIVE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *						
SAP MATERIAL No.:	0573719					
SHORT DESCRIPTION:	PADLOCK:ST OPER MASTER; YEL; NW OU					
TECH. DESCRIPTION:						
WEATHER PROOF PADLOCK * FOR NORTH-WEST OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * YELLOW RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: FIVE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *						
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED	P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013	
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.	VvZ	VvZ	C.D.SMITH	12/08/2004	
1	ALL PADLOCKS REPLACED AND KEYS ADDED	VvZ	VvZ	C.D.SMITH	6/5/02	
REV	REVISION DESCRIPTION	BY	CHKD	AUTH	DATE	REF. DRAWINGS
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE	<div> Eskom</div> <div>D-DT-6050</div> <div>SAP No: 0187170 0187171</div> <div>0573719</div> <div>SET SHEET REV</div> <div>45 9 3</div>	
				NTS		
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:		
				SERIES 6000		
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:		
				6050		


SPEC SHEET

SAP MATERIAL No.:		0187172						
SHORT DESCRIPTION:		PADLOCK, ST LIVE MASTER G OU D6050						
TECH. DESCRIPTION:								
WEATHER PROOF PADLOCK * FOR GAUTENG OPERATING UNIT ONLY *								
PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING *								
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *								
BLACK RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *								
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *								
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *								
MECHANISM: SIX PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *								
ESKOM DRAWING No. D-DT-6050 *								
SAP MATERIAL No.:		0187173						
SHORT DESCRIPTION:		PADLOCK, ST LIVE MASTER KZN OU D6050						
TECH. DESCRIPTION:								
WEATHER PROOF PADLOCK * FOR KWAZULU NATAL OPERATING UNIT ONLY *								
PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING *								
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *								
BLACK RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *								
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *								
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *								
MECHANISM: SIX PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *								
ESKOM DRAWING No. D-DT-6050 *								
SAP MATERIAL No.:		0187174						
SHORT DESCRIPTION:		PADLOCK, ST LIVE MASTER WC OU D6050						
TECH. DESCRIPTION:								
WEATHER PROOF PADLOCK * FOR WESTERN CAPE OPERATING UNIT ONLY *								
PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING *								
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *								
BLACK RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *								
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *								
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *								
MECHANISM: SIX PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *								
ESKOM DRAWING No. D-DT-6050 *								
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED			P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013	
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.			VvZ	VvZ	C.D.SMITH	12/08/2004	
1	ALL PADLOCKS REPLACED AND KEYS ADDED			VvZ	VvZ	C.D.SMITH	6/5/02	
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DRAWINGS
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE		<div> Eskom</div> <div>D-DT-6050</div>		
				NTS				
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:				
				SERIES 6000				
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:		SET		
				6050		SHEET		
						REV		
						45	10	3


SPEC SHEET

SAP MATERIAL No.:		0573493												
SHORT DESCRIPTION:		PADLOCK:ST LIVE MASTER; BLK; NC OU												
TECH. DESCRIPTION:														
PADLOCK: TYPE: ST LIVE MASTER; BLK; NC OU; SHACKLE DIAMETER: 6 MM; CASE SIZE: WD 40 X HT 38 X THK 20 MM; HORIZONTAL CLEARANCE: 20 MM; VERTICAL CLEARANCE: 30 MM; MATERIAL: LAMINATED STEEL WITH QUALITY ZINC PLATING; WEATHER PROOF PADLOCK; FOR NORTHERN CAPE OPERATING UNIT ONLY: BLACK RUBBER CASING; LOCKED BY DUAL STAINLESS STEEL BALL MECHANISM; NICKEL COATED 304 GRADE STAINLESS STEEL DIN 17224; MECHANISM: THREE PIN TUMBLER CYLINDER TYPE WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN; PIN SPRINGS: PHOSPHER BRONZE; ESKOM DRAWING No. D-DT-6050 *														
SAP MATERIAL No.:		0187175												
SHORT DESCRIPTION:		PADLOCK, ST LIVE MASTER EC OU D6050												
TECH. DESCRIPTION:														
WEATHER PROOF PADLOCK * FOR EASTERN CAPE OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * BLACK RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: SIX PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *														
SAP MATERIAL No.:		0187176												
SHORT DESCRIPTION:		PADLOCK, ST LIVE MASTER L OU D6050												
TECH. DESCRIPTION:														
WEATHER PROOF PADLOCK * FOR LIMPOPO OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * BLACK RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: SIX PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *														
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED				P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013						
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.				VvZ	VvZ	C.D.SMITH	12/08/2004						
1	ALL PADLOCKS REPLACED AND KEYS ADDED				VvZ	VvZ	C.D.SMITH	6/5/02						
REV	REVISION DESCRIPTION				BY	CHKD	AUTH	DATE	REF. DRAWINGS					
AUTH:		PHIL CROWDY	DATE:	03/98	SCALE NTS				SAP No:					
CHKD:		C.B. CLARK	DATE:	03/98	CAD REF:				0573493		0187176			
DRAWN:		J.F.SCHOLTZ	DATE:	02/98	SERIES 6000		D-DT-6050		SET		SHEET		REV	
					FILE No: 6050				45		11		3	


SPEC SHEET

SAP MATERIAL No.:		0187177									
SHORT DESCRIPTION:		PADLOCK, ST LIVE MASTER MP OU D6050									
TECH. DESCRIPTION:											
WEATHER PROOF PADLOCK * FOR MPUMALANGA OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * BLACK RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: SIX PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *											
SAP MATERIAL No.:		0187178									
SHORT DESCRIPTION:		PADLOCK, ST LIVE MASTER FS OU D6050									
TECH. DESCRIPTION:											
WEATHER PROOF PADLOCK * FOR FREE STATE OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * BLACK RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: SIX PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *											
SAP MATERIAL No.:		0573711									
SHORT DESCRIPTION:		PADLOCK:ST LIVE MASTER; BLK; NW OU									
TECH. DESCRIPTION:											
WEATHER PROOF PADLOCK * FOR NORTH-WEST OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * BLACK RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: SIX PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *											
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED			P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013				
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.			VvZ	VvZ	C.D.SMITH	12/08/2004				
1	ALL PADLOCKS REPLACED AND KEYS ADDED			VvZ	VvZ	C.D.SMITH	6/5/02				
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DRAWINGS			
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE	 D-DT-6050			SAP No:			
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:				0187177		0573711	
				SERIES 6000				SET	SHEET	REV	
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:				45	12	3	
				6050							


SPEC SHEET

SAP MATERIAL No.:		0187179								
SHORT DESCRIPTION:		PADLOCK, ST TSO MASTER G OU D6050								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR GAUTENG OPERATING UNIT ONLY *										
PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING *										
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *										
BLUE RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *										
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *										
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *										
MECHANISM: SEVEN PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *										
ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0187180								
SHORT DESCRIPTION:		PADLOCK, ST TSO MASTER KZN OU D6050								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR KWAZULU NATAL OPERATING UNIT ONLY *										
PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING *										
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *										
BLUE RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *										
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *										
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *										
MECHANISM: SEVEN PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *										
ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0187181								
SHORT DESCRIPTION:		PADLOCK, ST TSO MASTER WC OU D6050								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR WESTERN CAPE OPERATING UNIT ONLY *										
PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING *										
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *										
BLUE RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *										
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *										
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *										
MECHANISM: SEVEN PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *										
ESKOM DRAWING No. D-DT-6050 *										
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED			P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013			
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.			VvZ	VvZ	C.D.SMITH	12/08/2004			
1	ALL PADLOCKS REPLACED AND KEYS ADDED			VvZ	VvZ	C.D.SMITH	6/5/02			
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DRAWINGS		
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE NTS		 D-DT-6050		SAP No:		
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:				0187179	0187181	
				SERIES 6000				SET	SHEET	REV
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:				45	13	3
				6050						


SPEC SHEET

SAP MATERIAL No.:		0573494								
SHORT DESCRIPTION:		PADLOCK:ST TSO MASTER; BLU; NC OU								
TECH. DESCRIPTION:										
PADLOCK: TYPE: ST TSO MASTER; BLU; NC OU; SHACKLE DIAMETER: 6 MM; CASE SIZE: WD 40 X HT 38 X THK 20 MM; HORIZONTAL CLEARANCE: 20 MM; VERTICAL CLEARANCE: 30 MM; MATERIAL: LAMINATED STEEL WITH QUALITY ZINC PLATING; WEATHER PROOF PADLOCK; FOR NORTHERN CAPE OPERATING UNIT ONLY: BLUE RUBBER CASING; LOCKED BY DUAL STAINLESS STEEL BALL MECHANISM; NICKEL COATED 304 GRADE STAINLESS STEEL DIN 17224; MECHANISM: THREE PIN TUMBLER CYLINDER TYPE WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN; PIN SPRINGS: PHOSPHER BRONZE; ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0187182								
SHORT DESCRIPTION:		PADLOCK, ST TSO MASTER EC OU D6050								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR EASTERN CAPE OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * BLUE RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: SEVEN PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0187183								
SHORT DESCRIPTION:		PADLOCK, ST TSO MASTER L OU D6050								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR LIMPOPO OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * BLUE RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: SEVEN PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *										
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED			P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013			
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.			VvZ	VvZ	C.D.SMITH	12/08/2004			
1	ALL PADLOCKS REPLACED AND KEYS ADDED			VvZ	VvZ	C.D.SMITH	6/5/02			
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DRAWINGS		
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE NTS				SAP No:		
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:				0573494		0187183
				SERIES 6000				SET		
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:		D-DT-6050		45		
				6050				14		
								3		


SPEC SHEET

SAP MATERIAL No.:	0187184					
SHORT DESCRIPTION:	PADLOCK, ST TSO MASTER MP OU D6050					
TECH. DESCRIPTION:						
WEATHER PROOF PADLOCK * FOR MPUMALANGA OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * BLUE RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: SEVEN PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *						
SAP MATERIAL No.:	0187185					
SHORT DESCRIPTION:	PADLOCK, ST TSO MASTER FS OU D6050					
TECH. DESCRIPTION:						
WEATHER PROOF PADLOCK * FOR FREE STATE OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * BLUE RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: SEVEN PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *						
SAP MATERIAL No.:	0573712					
SHORT DESCRIPTION:	PADLOCK:ST TSO MASTER; BLU; NW OU					
TECH. DESCRIPTION:						
WEATHER PROOF PADLOCK * FOR NORTH-WEST OPERATING UNIT ONLY * PADLOCK BODY: 2mm THICK LAMINATED STEEL WITH QUALITY ZINC PLATING * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * BLUE RUBBER CASING * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: SEVEN PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *						
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED	P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013	
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.	VvZ	VvZ	C.D.SMITH	12/08/2004	
1	ALL PADLOCKS REPLACED AND KEYS ADDED	VvZ	VvZ	C.D.SMITH	6/5/02	
REV	REVISION DESCRIPTION	BY	CHKD	AUTH	DATE	REF. DRAWINGS
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE	<div> Eskom</div> <div>D-DT-6050</div>	
CHKD:	C.B. CLARK	DATE:	03/98	NTS		
				CAD REF:		
				SERIES 6000		
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:	<div>45</div> <div>15</div> <div>3</div>	
			6050			

SPEC SHEET

SAP MATERIAL No.:		0187236								
SHORT DESCRIPTION:		PADLOCK, NYLON LV MASTER G OU D6050								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR GAUTENG OPERATING UNIT ONLY *										
PADLOCK BODY: ORANGE FLAME RESISTANT GLASS RE-INFORCED NYLON *										
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *										
SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *										
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *										
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *										
MECHANISM: THREE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *										
ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0187237								
SHORT DESCRIPTION:		PADLOCK, NYLON LV MASTER KZN OU D6050								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR KWAZULU NATAL OPERATING UNIT ONLY *										
PADLOCK BODY: ORANGE FLAME RESISTANT GLASS RE-INFORCED NYLON *										
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *										
SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *										
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *										
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *										
MECHANISM: THREE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *										
ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0187238								
SHORT DESCRIPTION:		PADLOCK, NYLON LV MASTER WC OU D6050								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR WESTERN CAPE OPERATING UNIT ONLY *										
PADLOCK BODY: ORANGE FLAME RESISTANT GLASS RE-INFORCED NYLON *										
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *										
SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *										
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *										
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *										
MECHANISM: THREE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *										
ESKOM DRAWING No. D-DT-6050 *										
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED			P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013			
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.			VvZ	VvZ	C.D.SMITH	12/08/2004			
1	ALL PADLOCKS REPLACED AND KEYS ADDED			VvZ	VvZ	C.D.SMITH	6/5/02			
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DRAWINGS		
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE NTS				SAP No:		
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:				0187236	0187238	
				SERIES 6000				SET	SHEET	REV
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:		D-DT-6050		45	16	3
				6050						

SPEC SHEET

SAP MATERIAL No.:		0573495								
SHORT DESCRIPTION:		PADLOCK:NYL LV MASTER; ORG; NC OU								
TECH. DESCRIPTION:										
PADLOCK: TYPE: NYL GENERAL MASTER; ORG; NC OU; DIAMETER: 6 MM; CASE SIZE: WD 40 X HT 38 X THK 20 MM; HORIZONTAL CLEARANCE: 20 MM; VERTICAL CLEARANCE: 30 MM; MATERIAL: FLAME RESISTANT GLASS RE-INFORCED NYLON; WEATHER PROOF PADLOCK; FOR NORTHERN CAPE OPERATING UNIT ONLY: ORANGE RUBBER CASING; LOCKED BY DUAL STAINLESS STEEL BALL MECHANISM; NICKEL COATED 304 GRADE STAINLESS STEEL DIN 17224; MECHANISM: THREE PIN TUMBLER CYLINDER TYPE WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN; PIN SPRINGS: PHOSPHER BRONZE; ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0187239								
SHORT DESCRIPTION:		PADLOCK, NYLON LV MASTER, EC OU D6050								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR EASTERN CAPE OPERATING UNIT ONLY * PADLOCK BODY: ORANGE FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: THREE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0187240								
SHORT DESCRIPTION:		PADLOCK, NYLON LV MASTER L OU D6050								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR LIMPOPO OPERATING UNIT ONLY * PADLOCK BODY: ORANGE FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: THREE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *										
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED			P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013			
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.			VvZ	VvZ	C.D.SMITH	12/08/2004			
1	ALL PADLOCKS REPLACED AND KEYS ADDED			VvZ	VvZ	C.D.SMITH	6/5/02			
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DRAWINGS		
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE NTS		 D-DT-6050		SAP No:		
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:				0573495	0187240	
				SERIES 6000				SET		SHEET
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No: 6050				45	17	3

SPEC SHEET

SAP MATERIAL No.:	0187241
SHORT DESCRIPTION:	PADLOCK, NYLON LV MASTER MP OU D6050
TECH. DESCRIPTION:	
WEATHER PROOF PADLOCK * FOR MPUMALANGA OPERATING UNIT ONLY * PADLOCK BODY: ORANGE FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: THREE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *	
SAP MATERIAL No.:	0187242
SHORT DESCRIPTION:	PADLOCK, NYLON LV MASTER FS OU D6050
TECH. DESCRIPTION:	
WEATHER PROOF PADLOCK * FOR FREE STATE OPERATING UNIT ONLY * PADLOCK BODY: ORANGE FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: THREE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *	
SAP MATERIAL No.:	0573720
SHORT DESCRIPTION:	PADLOCK:NYL LV MASTER; ORG; NW OU
TECH. DESCRIPTION:	
WEATHER PROOF PADLOCK * FOR NORTH-WEST OPERATING UNIT ONLY * PADLOCK BODY: ORANGE FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: THREE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *	


3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED	P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013		
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.	VvZ	VvZ	C.D.SMITH	12/08/2004		
1	ALL PADLOCKS REPLACED AND KEYS ADDED	VvZ	VvZ	C.D.SMITH	6/5/02		
REV	REVISION DESCRIPTION	BY	CHKD	AUTH	DATE	REF. DRAWINGS	
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE	SAP No: 0187241 0187242		
				NTS			
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:	0573720		
				SERIES 6000			
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:	D-DT-6050		
				6050			
					SET	SHEET	REV
					45	18	3

SPEC SHEET


SAP MATERIAL No.:	0573722
SHORT DESCRIPTION:	PADLOCK, NYLON PROH MASTER G OU D6050
TECH. DESCRIPTION:	
WEATHER PROOF PADLOCK * FOR GAUTENG OPERATING UNIT ONLY * PADLOCK BODY: GREEN FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: FOUR PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *	
SAP MATERIAL No.:	0187244
SHORT DESCRIPTION:	PADLOCK, NYLON PROH MASTER KZN OU D6050
TECH. DESCRIPTION:	
WEATHER PROOF PADLOCK * FOR KWAZULU NATAL OPERATING UNIT ONLY * PADLOCK BODY: GREEN FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: FOUR PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *	
SAP MATERIAL No.:	0187245
SHORT DESCRIPTION:	PADLOCK, NYLON PROH MASTER WC OU D6050
TECH. DESCRIPTION:	
WEATHER PROOF PADLOCK * FOR WESTERN CAPE OPERATING UNIT ONLY * PADLOCK BODY: GREEN FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: FOUR PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *	
Mal please check SAP for number	

3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED	P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013		
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.	VvZ	VvZ	C.D.SMITH	12/08/2004		
1	ALL PADLOCKS REPLACED AND KEYS ADDED	VvZ	VvZ	C.D.SMITH	6/5/02		
REV	REVISION DESCRIPTION	BY	CHKD	AUTH	DATE	REF. DRAWINGS	
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE	SAP No: 0573722		
				NTS			
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:	0187245 0187244		
				SERIES 6000			
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:	D-DT-6050		
				6050			
					SET	SHEET	REV
					45	19	3

SPEC SHEET


SAP MATERIAL No.:		0573496									
SHORT DESCRIPTION:		PADLOCK:NYL PROH MASTER; GRN; NC OU									
TECH. DESCRIPTION:											
PADLOCK: TYPE: NYL PROH MASTER; GRN; NC OU; SHACKLE DIAMETER: 6 MM; CASE SIZE: WD 40 X HT 38 X THK 20 MM; HORIZONTAL CLEARANCE: 20 MM; VERTICAL CLEARANCE: 30 MM; MATERIAL: FLAME RESISTANT GLASS RE-INFORCED NYLON; WEATHER PROOF PADLOCK; FOR NORTHERN CAPE OPERATING UNIT ONLY: GREEN RUBBER CASING; LOCKED BY DUAL STAINLESS STEEL BALL MECHANISM; NICKEL COATED 304 GRADE STAINLESS STEEL DIN 17224; MECHANISM: THREE PIN TUMBLER CYLINDER TYPE WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN; PIN SPRINGS: PHOSPHER BRONZE; ESKOM DRAWING No. D-DT-6050 *											
SAP MATERIAL No.:		0187246									
SHORT DESCRIPTION:		PADLOCK, NYLON PROH MASTER EC OU D6050									
TECH. DESCRIPTION:											
WEATHER PROOF PADLOCK * FOR EASTERN CAPE OPERATING UNIT ONLY * PADLOCK BODY: GREEN FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: FOUR PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *											
SAP MATERIAL No.:		0187247									
SHORT DESCRIPTION:		PADLOCK, NYLON PROH MASTER L OU D6050									
TECH. DESCRIPTION:											
WEATHER PROOF PADLOCK * FOR LIMPOPO OPERATING UNIT ONLY * PADLOCK BODY: GREEN FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: FOUR PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *											
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED			P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013				
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.			VvZ	VvZ	C.D.SMITH	12/08/2004				
1	ALL PADLOCKS REPLACED AND KEYS ADDED			VvZ	VvZ	C.D.SMITH	6/5/02				
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DRAWINGS			
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE NTS		 D-DT-6050		SAP No: 0573496 0187246		0187247	
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF: SERIES 6000				SET	SHEET		REV
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No: 6050				45	20		3

SPEC SHEET


SAP MATERIAL No.:		0187248								
SHORT DESCRIPTION:		PADLOCK, NYLON PROH MASTER MP OU D6050								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR MPUMALANGA OPERATING UNIT ONLY * PADLOCK BODY: GREEN FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: FOUR PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0187249								
SHORT DESCRIPTION:		PADLOCK, NYLON PROH MASTER FS OU D6050								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR FREE STATE OPERATING UNIT ONLY * PADLOCK BODY: GREEN FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: FOUR PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0573713								
SHORT DESCRIPTION:		PADLOCK:NYL PROH MASTER; GRN; NW OU								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR NORTH-WEST OPERATING UNIT ONLY * PADLOCK BODY: GREEN FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: FOUR PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *										
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED				P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013		
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.				VvZ	VvZ	C.D.SMITH	12/08/2004		
1	ALL PADLOCKS REPLACED AND KEYS ADDED				VvZ	VvZ	C.D.SMITH	6/5/02		
REV	REVISION DESCRIPTION				BY	CHKD	AUTH	DATE	REF. DRAWINGS	
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE	 D-DT-6050			SAP No:		
CHKD:	C.B. CLARK	DATE:	03/98	NTS				0187248		0573713
				CAD REF:				0187249		
				SERIES 6000				SET SHEET REV		
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:				45	21	3
				6050						

SPEC SHEET

SAP MATERIAL No.:		0187250					
SHORT DESCRIPTION:		PADLOCK, NYLON OPER MASTER G OU D6050					
TECH. DESCRIPTION:							
WEATHER PROOF PADLOCK * FOR GAUTENG OPERATING UNIT ONLY *							
PADLOCK BODY: YELLOW FLAME RESISTANT GLASS RE-INFORCED NYLON *							
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *							
SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *							
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *							
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *							
MECHANISM: FIVE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *							
ESKOM DRAWING No. D-DT-6050 *							
SAP MATERIAL No.:		0187251					
SHORT DESCRIPTION:		PADLOCK, NYLON OPER MASTER KZN OU D6050					
TECH. DESCRIPTION:							
WEATHER PROOF PADLOCK * FOR KWAZULU NATAL OPERATING UNIT ONLY *							
PADLOCK BODY: YELLOW FLAME RESISTANT GLASS RE-INFORCED NYLON *							
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *							
SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *							
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *							
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *							
MECHANISM: FIVE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *							
ESKOM DRAWING No. D-DT-6050 *							
SAP MATERIAL No.:		0187252					
SHORT DESCRIPTION:		PADLOCK, NYLON OPER MASTER WC OU D6050					
TECH. DESCRIPTION:							
WEATHER PROOF PADLOCK * FOR WESTERN CAPE OPERATING UNIT ONLY *							
PADLOCK BODY: YELLOW FLAME RESISTANT GLASS RE-INFORCED NYLON *							
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *							
SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *							
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *							
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *							
MECHANISM: FIVE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *							
ESKOM DRAWING No. D-DT-6050 *							


3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED		P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013		
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.		VvZ	VvZ	C.D.SMITH	12/08/2004		
1	ALL PADLOCKS REPLACED AND KEYS ADDED		VvZ	VvZ	C.D.SMITH	6/5/02		
REV	REVISION DESCRIPTION		BY	CHKD	AUTH	DATE	REF. DRAWINGS	
AUTH:	PHIL CROWDY	DATE:	03/98	 D-DT-6050		SAP No:		
CHKD:	C.B. CLARK	DATE:	03/98			0187250	0187252	
						0187251		
DRAWN:	J.F.SCHOLTZ	DATE:	02/98			SET	SHEET	REV
						45	22	3

SPEC SHEET


SAP MATERIAL No.:		0573497									
SHORT DESCRIPTION:		PADLOCK:NYL OPER MASTER; YEL; NC OU									
TECH. DESCRIPTION:											
PADLOCK: TYPE: NYL OPER MASTER; YEL; NC OU; SHACKLE DIAMETER: 6 MM; CASE SIZE: WD 40 X HT 38 X THK 20 MM; HORIZONTAL CLEARANCE: 20 MM; VERTICAL CLEARANCE: 30 MM; MATERIAL: FLAME RESISTANT GLASS RE-INFORCED NYLON; WEATHER PROOF PADLOCK; FOR NORTHERN CAPE OPERATING UNIT ONLY: YELLOW RUBBER CASING; LOCKED BY DUAL STAINLESS STEEL BALL MECHANISM; NICKEL COATED 304 GRADE STAINLESS STEEL DIN 17224; MECHANISM: THREE PIN TUMBLER CYLINDER TYPE WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN; PIN SPRINGS: PHOSPHER BRONZE; ESKOM DRAWING No. D-DT-6050 *											
SAP MATERIAL No.:		0187253									
SHORT DESCRIPTION:		PADLOCK, NYLON OPER MASTER EC OU D6050									
TECH. DESCRIPTION:											
WEATHER PROOF PADLOCK * FOR EASTERN CAPE OPERATING UNIT ONLY * PADLOCK BODY: YELLOW FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: FIVE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *											
SAP MATERIAL No.:		0187254									
SHORT DESCRIPTION:		PADLOCK, NYLON OPER MASTER L OU D6050									
TECH. DESCRIPTION:											
WEATHER PROOF PADLOCK * FOR LIMPOPO OPERATING UNIT ONLY * PADLOCK BODY: YELLOW FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: FIVE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *											
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED			P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013				
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.			VvZ	VvZ	C.D.SMITH	12/08/2004				
1	ALL PADLOCKS REPLACED AND KEYS ADDED			VvZ	VvZ	C.D.SMITH	6/5/02				
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DRAWINGS			
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE NTS		 D-DT-6050		SAP No: 0573497 0187253		0187254	
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF: SERIES 6000				SET	SHEET		REV
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No: 6050				45	23		3

SPEC SHEET


SAP MATERIAL No.:	0187255
SHORT DESCRIPTION:	PADLOCK, NYLON OPER MASTER MP OU D6050
TECH. DESCRIPTION:	
WEATHER PROOF PADLOCK * FOR MPUMALANGA OPERATING UNIT ONLY * PADLOCK BODY: YELLOW FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: FIVE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *	
SAP MATERIAL No.:	0187256
SHORT DESCRIPTION:	PADLOCK, NYLON OPER MASTER FS OU D6050
TECH. DESCRIPTION:	
WEATHER PROOF PADLOCK * FOR FREE STATE OPERATING UNIT ONLY * PADLOCK BODY: YELLOW FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: FIVE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *	
SAP MATERIAL No.:	0573714
SHORT DESCRIPTION:	PADLOCK:NYL OPER MASTER; YEL; NW OU
TECH. DESCRIPTION:	
WEATHER PROOF PADLOCK * FOR NORTH-WEST OPERATING UNIT ONLY * PADLOCK BODY: YELLOW FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: FIVE PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *	

3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED	P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013	
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.	VvZ	VvZ	C.D.SMITH	12/08/2004	
1	ALL PADLOCKS REPLACED AND KEYS ADDED	VvZ	VvZ	C.D.SMITH	6/5/02	
REV	REVISION DESCRIPTION	BY	CHKD	AUTH	DATE	REF. DRAWINGS
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE	<div> Eskom</div> <div>D-DT-6050</div>	
				NTS		
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:		
				SERIES 6000		
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:	SAP No: 0187255 0187256	
				6050		
					SET	SHEET
					45	24
						REV
						3


SPEC SHEET

SAP MATERIAL No.:		0187257							
SHORT DESCRIPTION:		PADLOCK, NYLON LIVE OU MASTER G OU D6050							
TECH. DESCRIPTION:									
WEATHER PROOF PADLOCK * FOR GAUTENG OPERATING UNIT ONLY *									
PADLOCK BODY: BLACK FLAME RESISTANT GLASS RE-INFORCED NYLON *									
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *									
SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *									
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *									
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *									
MECHANISM: SIX PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *									
ESKOM DRAWING No. D-DT-6050 *									
SAP MATERIAL No.:		0187258							
SHORT DESCRIPTION:		PADLOCK, NYLON LIVE MASTER KZN OU D6050							
TECH. DESCRIPTION:									
WEATHER PROOF PADLOCK * FOR KWAZULU NATAL OPERATING UNIT ONLY *									
PADLOCK BODY: BLACK FLAME RESISTANT GLASS RE-INFORCED NYLON *									
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *									
SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *									
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *									
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *									
MECHANISM: SIX PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *									
ESKOM DRAWING No. D-DT-6050 *									
SAP MATERIAL No.:		0187259							
SHORT DESCRIPTION:		PADLOCK, NYLON LIVE MASTER WC OU D6050							
TECH. DESCRIPTION:									
WEATHER PROOF PADLOCK * FOR WESTERN CAPE OPERATING UNIT ONLY *									
PADLOCK BODY: BLACK FLAME RESISTANT GLASS RE-INFORCED NYLON *									
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *									
SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *									
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *									
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *									
MECHANISM: SIX PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *									
ESKOM DRAWING No. D-DT-6050 *									
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED			P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013		
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.			VvZ	VvZ	C.D.SMITH	12/08/2004		
1	ALL PADLOCKS REPLACED AND KEYS ADDED			VvZ	VvZ	C.D.SMITH	6/5/02		
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DRAWINGS	
AUTH:		PHIL CROWDY	DATE:	03/98	 D-DT-6050		SAP No:		
CHKD:		C.B. CLARK	DATE:	03/98			0187257		0187259
DRAWN:		J.F.SCHOLTZ		DATE:			02/98		
						SET		SHEET	REV
						45		25	3


SPEC SHEET

SAP MATERIAL No.:		0573498						
SHORT DESCRIPTION:		PADLOCK:NYL LIVE MASTER; BLK; NC OU						
TECH. DESCRIPTION:								
PADLOCK: TYPE: NYL LIVE MASTER; BLK; NC OU; SHACKLE DIAMETER: 6 MM; CASE SIZE: WD 40 X HT 38 X THK 20 MM; HORIZONTAL CLEARANCE: 20 MM; VERTICAL CLEARANCE: 30 MM; MATERIAL: FLAME RESISTANT GLASS RE-INFORCED NYLON; WEATHER PROOF PADLOCK; FOR NORTHERN CAPE OPERATING UNIT ONLY: BLACK RUBBER CASING; LOCKED BY DUAL STAINLESS STEEL BALL MECHANISM; NICKEL COATED 304 GRADE STAINLESS STEEL DIN 17224; MECHANISM: THREE PIN TUMBLER CYLINDER TYPE WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN; PIN SPRINGS: PHOSPHER BRONZE; ESKOM DRAWING No. D-DT-6050 *								
SAP MATERIAL No.:		0187260						
SHORT DESCRIPTION:		PADLOCK, NYLON LIVE MASTER EC OU D6050						
TECH. DESCRIPTION:								
WEATHER PROOF PADLOCK * FOR EASTERN CAPE OPERATING UNIT ONLY * PADLOCK BODY: BLACK FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: SIX PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *								
SAP MATERIAL No.:		0187261						
SHORT DESCRIPTION:		PADLOCK, NYLON LIVE MASTER L OU D6050						
TECH. DESCRIPTION:								
WEATHER PROOF PADLOCK * FOR LIMPOPO OPERATING UNIT ONLY * PADLOCK BODY: BLACK FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: SIX PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *								
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED			P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013	
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.			VvZ	VvZ	C.D.SMITH	12/08/2004	
1	ALL PADLOCKS REPLACED AND KEYS ADDED			VvZ	VvZ	C.D.SMITH	6/5/02	
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DRAWINGS
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE NTS		 D-DT-6050		
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:				
				SERIES 6000				
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:		SET	SHEET	REV
				6050		45	26	3


SPEC SHEET

SAP MATERIAL No.:	0187262					
SHORT DESCRIPTION:	PADLOCK, NYLON LIVE MASTER MP OU D6050					
TECH. DESCRIPTION:						
WEATHER PROOF PADLOCK * FOR MPUMALANGA OPERATING UNIT ONLY * PADLOCK BODY: BLACK FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: SIX PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *						
SAP MATERIAL No.:	0187263					
SHORT DESCRIPTION:	PADLOCK, NYLON LIVE MASTER FS OU D6050					
TECH. DESCRIPTION:						
WEATHER PROOF PADLOCK * FOR FREE STATE OPERATING UNIT ONLY * PADLOCK BODY: BLACK FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: SIX PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *						
SAP MATERIAL No.:	0573715					
SHORT DESCRIPTION:	PADLOCK:NYL LIVE MASTER; BLK; NW OU					
TECH. DESCRIPTION:						
WEATHER PROOF PADLOCK * FOR NORTH-WEST OPERATING UNIT ONLY * PADLOCK BODY: BLACK FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: SIX PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *						
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED	P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013	
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.	VvZ	VvZ	C.D.SMITH	12/08/2004	
1	ALL PADLOCKS REPLACED AND KEYS ADDED	VvZ	VvZ	C.D.SMITH	6/5/02	
REV	REVISION DESCRIPTION	BY	CHKD	AUTH	DATE	REF. DRAWINGS
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE	<div> Eskom</div> <div>D-DT-6050</div>	
CHKD:	C.B. CLARK	DATE:	03/98	NTS		
				CAD REF:		
				SERIES 6000		
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:	<div>45</div> <div>27</div> <div>3</div>	
				6050		

SPEC SHEET


SAP MATERIAL No.:		0187264								
SHORT DESCRIPTION:		PADLOCK, NYLON TSO MASTER G OU D6050								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR GAUTENG OPERATING UNIT ONLY *										
PADLOCK BODY: BLUE FLAME RESISTANT GLASS RE-INFORCED NYLON *										
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *										
SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *										
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *										
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *										
MECHANISM: SEVEN PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *										
ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0187265								
SHORT DESCRIPTION:		PADLOCK, NYLON TSO MASTER KZN OU D6050								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR KWAZULU NATAL OPERATING UNIT ONLY *										
PADLOCK BODY: BLUE FLAME RESISTANT GLASS RE-INFORCED NYLON *										
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *										
SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *										
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *										
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *										
MECHANISM: SEVEN PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *										
ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0187266								
SHORT DESCRIPTION:		PADLOCK, NYLON TSO MASTER WC OU D6050								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR WESTERN CAPE OPERATING UNIT ONLY *										
PADLOCK BODY: BLUE FLAME RESISTANT GLASS RE-INFORCED NYLON *										
DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm *										
SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm *										
LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM *										
SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 *										
MECHANISM: SEVEN PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE *										
ESKOM DRAWING No. D-DT-6050 *										
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED			P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013			
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.			VvZ	VvZ	C.D.SMITH	12/08/2004			
1	ALL PADLOCKS REPLACED AND KEYS ADDED			VvZ	VvZ	C.D.SMITH	6/5/02			
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DRAWINGS		
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE NTS		 D-DT-6050		SAP No:		
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:				0187264	0187266	
				SERIES 6000				SET	SHEET	REV
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:				45	28	3
				6050						

SPEC SHEET


SAP MATERIAL No.:		0573499								
SHORT DESCRIPTION:		PADLOCK:NYL TSO MASTER; BLU; NC OU								
TECH. DESCRIPTION:										
PADLOCK: TYPE: NYL TSO MASTER; BLU; NC OU; SHACKLE DIAMETER: 6 MM; CASE SIZE: WD 40 X HT 38 X THK 20 MM; HORIZONTAL CLEARANCE: 20 MM; VERTICAL CLEARANCE: 30 MM; MATERIAL: FLAME RESISTANT GLASS RE-INFORCED NYLON; WEATHER PROOF PADLOCK; FOR NORTHERN CAPE OPERATING UNIT ONLY: BLUE RUBBER CASING; LOCKED BY DUAL STAINLESS STEEL BALL MECHANISM; NICKEL COATED 304 GRADE STAINLESS STEEL DIN 17224; MECHANISM: THREE PIN TUMBLER CYLINDER TYPE WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN; PIN SPRINGS: PHOSPHER BRONZE; ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0187267								
SHORT DESCRIPTION:		PADLOCK, NYLON TSO MASTER EC OU D6050								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR EASTERN CAPE OPERATING UNIT ONLY * PADLOCK BODY: BLUE FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: SEVEN PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0187268								
SHORT DESCRIPTION:		PADLOCK, NYLON TSO MASTER L OU D6050								
TECH. DESCRIPTION:										
WEATHER PROOF PADLOCK * FOR LIMPOPO OPERATING UNIT ONLY * PADLOCK BODY: BLUE FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: SEVEN PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *										
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED			P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013			
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.			VvZ	VvZ	C.D.SMITH	12/08/2004			
1	ALL PADLOCKS REPLACED AND KEYS ADDED			VvZ	VvZ	C.D.SMITH	6/5/02			
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DRAWINGS		
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE NTS				SAP No:		
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:				0573499		0187268
				SERIES 6000				SET		
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:		D-DT-6050		45	29	3
				6050						

SPEC SHEET

SAP MATERIAL No.:	0187269
SHORT DESCRIPTION:	PADLOCK, NYLON TSO MASTER MP OU D6050
TECH. DESCRIPTION:	
WEATHER PROOF PADLOCK * FOR MPUMALANGA OPERATING UNIT ONLY * PADLOCK BODY: BLUE FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: SEVEN PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *	
SAP MATERIAL No.:	0187270
SHORT DESCRIPTION:	PADLOCK, NYLON TSO MASTER FS OU D6050
TECH. DESCRIPTION:	
WEATHER PROOF PADLOCK * FOR FREE STATE OPERATING UNIT ONLY * PADLOCK BODY: BLUE FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: SEVEN PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *	
SAP MATERIAL No.:	0573721
SHORT DESCRIPTION:	PADLOCK:NYL TSO MASTER; BLU; NW OU
TECH. DESCRIPTION:	
WEATHER PROOF PADLOCK * FOR NORTH-WEST OPERATING UNIT ONLY * PADLOCK BODY: BLUE FLAME RESISTANT GLASS RE-INFORCED NYLON * DIMENSIONS: HEIGHT: MAXIMUM 25-38mm, WIDTH: 28-40mm, THICKNESS: 18-20mm * SHACKLES: DIA 6mm, LENGTH 30-34mm, WIDTH: 20mm * LOCKING BY DUAL STAINLESS STEEL BALL MECHANISM * SHACKLE SPRINGS NICKEL COATED 304-GRADE STAINLESS STEEL DIN 17224 * MECHANISM: SEVEN PIN TUMBLER CYLINDER TYPE, WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN * PIN SPRINGS: PHOSPHER BRONZE * ESKOM DRAWING No. D-DT-6050 *	

3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED	P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013	
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.	VvZ	VvZ	C.D.SMITH	12/08/2004	
1	ALL PADLOCKS REPLACED AND KEYS ADDED	VvZ	VvZ	C.D.SMITH	6/5/02	
REV	REVISION DESCRIPTION	BY	CHKD	AUTH	DATE	REF. DRAWINGS
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE	<div> Eskom</div> <div>D-DT-6050</div>	
CHKD:	C.B. CLARK	DATE:	03/98	NTS		
				CAD REF:		
				SERIES 6000		
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:	<div>SET</div> <div>45</div>	
				6050		
					<div>REV</div> <div>3</div>	


SPEC SHEET

SAP MATERIAL No.:		0573482						
SHORT DESCRIPTION:		PADLOCK:ST GENERAL MASTER; WHT; G OU						
TECH. DESCRIPTION:								
PADLOCK: TYPE: ST GENERAL MASTER; WHT; G OU; SHACKLE DIAMETER: 6 MM; CASE SIZE: WD 40 X HT 38 X THK 20 MM; HORIZONTAL CLEARANCE: 20 MM; VERTICAL CLEARANCE: 30 MM; MATERIAL: LAMINATED STEEL WITH QUALITY ZINC PLATING; WEATHER PROOF PADLOCK; FOR GAUTENG OPERATING UNIT ONLY; WHITE RUBBER CASING; LOCKED BY DUAL STAINLESS STEEL BALL MECHANISM; NICKEL COATED 304 GRADE STAINLESS STEEL DIN 17224; MECHANISM: THREE PIN TUMBLER CYLINDER TYPE WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN; PIN SPRINGS: PHOSPHER BRONZE; ESKOM DRAWING No. D-DT-6050 *								
SAP MATERIAL No.:		0573533						
SHORT DESCRIPTION:		PADLOCK:ST GENERAL MASTER; WHT; KZN OU						
TECH. DESCRIPTION:								
PADLOCK: TYPE: ST GENERAL MASTER; WHT; KZN OU; SHACKLE DIAMETER: 6 MM; CASE SIZE: WD 40 X HT 38 X THK 20 MM; HORIZONTAL CLEARANCE: 20 MM; VERTICAL CLEARANCE: 30 MM; MATERIAL: LAMINATED STEEL WITH QUALITY ZINC PLATING; WEATHER PROOF PADLOCK; FOR KWAZULU NATAL OPERATING UNIT ONLY: WHITE RUBBER CASING; LOCKED BY DUAL STAINLESS STEEL BALL MECHANISM; NICKEL COATED 304 GRADE STAINLESS STEEL DIN 17224; MECHANISM: THREE PIN TUMBLER CYLINDER TYPE WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN; PIN SPRINGS: PHOSPHER BRONZE; ESKOM DRAWING No. D-DT-6050 *								
SAP MATERIAL No.:		0573483						
SHORT DESCRIPTION:		PADLOCK:ST GENERAL MASTER; WHT; WC OU						
TECH. DESCRIPTION:								
PADLOCK: TYPE: ST GENERAL MASTER; WHT; WC OU; SHACKLE DIAMETER: 6 MM; CASE SIZE: WD 40 X HT 38 X THK 20 MM; HORIZONTAL CLEARANCE: 20 MM; VERTICAL CLEARANCE: 30 MM; MATERIAL: LAMINATED STEEL WITH QUALITY ZINC PLATING; WEATHER PROOF PADLOCK; FOR WESTERN CAPE OPERATING UNIT ONLY; WHITE RUBBER CASING; LOCKED BY DUAL STAINLESS STEEL BALL MECHANISM; NICKEL COATED 304 GRADE STAINLESS STEEL DIN 17224; MECHANISM: THREE PIN TUMBLER CYLINDER TYPE WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN; PIN SPRINGS: PHOSPHER BRONZE; ESKOM DRAWING No. D-DT-6050 *								
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED			P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013	
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.			VvZ	VvZ	C.D.SMITH	12/08/2004	
1	ALL PADLOCKS REPLACED AND KEYS ADDED			VvZ	VvZ	C.D.SMITH	6/5/02	
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DRAWINGS
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE		<div> Eskom</div> <div>D-DT-6050</div>		
CHKD:	C.B. CLARK	DATE:	03/98	NTS				
				CAD REF:				
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	SERIES 6000		SET	SHEET	REV
				FILE No:		45	31	3
				6050				

SPEC SHEET

SAP MATERIAL No.:		0573484						
SHORT DESCRIPTION:		PADLOCK:ST GENERAL MASTER; WHT; NC OU						
TECH. DESCRIPTION:								
PADLOCK: TYPE: ST GENERAL MASTER; WHT; NC OU; SHACKLE DIAMETER: 6 MM; CASE SIZE: WD 40 X HT 38 X THK 20 MM; HORIZONTAL CLEARANCE: 20 MM; VERTICAL CLEARANCE: 30 MM; MATERIAL: LAMINATED STEEL WITH QUALITY ZINC PLATING; WEATHER PROOF PADLOCK; FOR NORTHERN CAPE OPERATING UNIT ONLY; WHITE RUBBER CASING; LOCKED BY DUAL STAINLESS STEEL BALL MECHANISM; NICKEL COATED 304 GRADE STAINLESS STEEL DIN 17224; MECHANISM: THREE PIN TUMBLER CYLINDER TYPE WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN; PIN SPRINGS: PHOSPHER BRONZE; ESKOM DRAWING No. D-DT-6050 *								
SAP MATERIAL No.:		0573485						
SHORT DESCRIPTION:		PADLOCK:ST GENERAL MASTER; WHT; EC OU						
TECH. DESCRIPTION:								
PADLOCK: TYPE: ST GENERAL MASTER; WHT; EC OU; SHACKLE DIAMETER: 6 MM; CASE SIZE: WD 40 X HT 38 X THK 20 MM; HORIZONTAL CLEARANCE: 20 MM; VERTICAL CLEARANCE: 30 MM; MATERIAL: LAMINATED STEEL WITH QUALITY ZINC PLATING; WEATHER PROOF PADLOCK; FOR EASTERN CAPE OPERATING UNIT ONLY; WHITE RUBBER CASING; LOCKED BY DUAL STAINLESS STEEL BALL MECHANISM; NICKEL COATED 304 GRADE STAINLESS STEEL DIN 17224; MECHANISM: THREE PIN TUMBLER CYLINDER TYPE WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN; PIN SPRINGS: PHOSPHER BRONZE; ESKOM DRAWING No. D-DT-6050 *								
SAP MATERIAL No.:		0573486						
SHORT DESCRIPTION:		PADLOCK:ST GENERAL MASTER; WHT; L OU						
TECH. DESCRIPTION:								
PADLOCK: TYPE: ST GENERAL MASTER; WHT; L OU; SHACKLE DIAMETER: 6 MM; CASE SIZE: WD 40 X HT 38 X THK 20 MM; HORIZONTAL CLEARANCE: 20 MM; VERTICAL CLEARANCE: 30 MM; MATERIAL: LAMINATED STEEL WITH QUALITY ZINC PLATING; WEATHER PROOF PADLOCK; FOR LIMPOPO OPERATING UNIT ONLY; WHITE RUBBER CASING; LOCKED BY DUAL STAINLESS STEEL BALL MECHANISM; NICKEL COATED 304 GRADE STAINLESS STEEL DIN 17224; MECHANISM: THREE PIN TUMBLER CYLINDER TYPE WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN; PIN SPRINGS: PHOSPHER BRONZE; ESKOM DRAWING No. D-DT-6050 *								
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED			P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013	
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.			VvZ	VvZ	C.D.SMITH	12/08/2004	
1	ALL PADLOCKS REPLACED AND KEYS ADDED			VvZ	VvZ	C.D.SMITH	6/5/02	
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DRAWINGS
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE		SAP No:		
				NTS		0573484		
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:		0573485		
				SERIES 6000		0573486		
				FILE No:		SET SHEET REV		
				6050		45 32 3		
D-DT-6050								

SPEC SHEET

SAP MATERIAL No.:		0573487						
SHORT DESCRIPTION:		PADLOCK:ST GENERAL MASTER; WHT; MP OU						
TECH. DESCRIPTION:								
PADLOCK: TYPE: ST GENERAL MASTER; WHT; MP OU; SHACKLE DIAMETER: 6 MM; CASE SIZE: WD 40 X HT 38 X THK 20 MM; HORIZONTAL CLEARANCE: 20 MM; VERTICAL CLEARANCE: 30 MM; MATERIAL: LAMINATED STEEL WITH QUALITY ZINC PLATING; WEATHER PROOF PADLOCK; FOR MPUMALANGA OPERATING UNIT ONLY; WHITE RUBBER CASING; LOCKED BY DUAL STAINLESS STEEL BALL MECHANISM; NICKEL COATED 304 GRADE STAINLESS STEEL DIN 17224; MECHANISM: THREE PIN TUMBLER CYLINDER TYPE WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN; PIN SPRINGS: PHOSPHER BRONZE; ESKOM DRAWING No. D-DT-6050 *								
SAP MATERIAL No.:		0573488						
SHORT DESCRIPTION:		PADLOCK:ST GENERAL MASTER; WHT; NW OU						
TECH. DESCRIPTION:								
PADLOCK: TYPE: ST GENERAL MASTER; WHT; NW OU; SHACKLE DIAMETER: 6 MM; CASE SIZE: WD 40 X HT 38 X THK 20 MM; HORIZONTAL CLEARANCE: 20 MM; VERTICAL CLEARANCE: 30 MM; MATERIAL: LAMINATED STEEL WITH QUALITY ZINC PLATING; WEATHER PROOF PADLOCK; FOR NORTH WEST OPERATING UNIT ONLY; WHITE RUBBER CASING; LOCKED BY DUAL STAINLESS STEEL BALL MECHANISM; NICKEL COATED 304 GRADE STAINLESS STEEL DIN 17224; MECHANISM: THREE PIN TUMBLER CYLINDER TYPE WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN; PIN SPRINGS: PHOSPHER BRONZE; ESKOM DRAWING No. D-DT-6050 *								
SAP MATERIAL No.:		0573489						
SHORT DESCRIPTION:		PADLOCK:ST GENERAL MASTER; WHT; FS OU						
TECH. DESCRIPTION:								
PADLOCK: TYPE: ST GENERAL MASTER; WHT; FS OU; SHACKLE DIAMETER: 6 MM; CASE SIZE: WD 40 X HT 38 X THK 20 MM; HORIZONTAL CLEARANCE: 20 MM; VERTICAL CLEARANCE: 30 MM; MATERIAL: LAMINATED STEEL WITH QUALITY ZINC PLATING; WEATHER PROOF PADLOCK; FOR FREE STATE OPERATING UNIT ONLY; WHITE RUBBER CASING; LOCKED BY DUAL STAINLESS STEEL BALL MECHANISM; NICKEL COATED 304 GRADE STAINLESS STEEL DIN 17224; MECHANISM: THREE PIN TUMBLER CYLINDER TYPE WITH FOUR ANTI-PICK MUSHROOM PINS AND SECURITY PLATE OR PIN; PIN SPRINGS: PHOSPHER BRONZE; ESKOM DRAWING No. D-DT-6050 *								
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED			P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013	
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.			VvZ	VvZ	C.D.SMITH	12/08/2004	
1	ALL PADLOCKS REPLACED AND KEYS ADDED			VvZ	VvZ	C.D.SMITH	6/5/02	
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DRAWINGS
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE		<div> Eskom</div> <div>D-DT-6050</div>		
CHKD:	C.B. CLARK	DATE:	03/98	NTS				
				CAD REF:				
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	SERIES 6000		SET		SHEET
				FILE No:		45		33
				6050		3		

SPEC SHEET

SAP MATERIAL No.:		0187186					
SHORT DESCRIPTION:		KEY, PADLOCK, LV MASTER, G OU D6050					
TECH. DESCRIPTION:							
KEY FOR WEATHER PROOF PADLOCK * FOR GAUTENG OPERATING UNIT ONLY *							
MATERIAL: BRASS * COLOUR: ORANGE * IDENTIFICATION CODE: 2.5mm HIGH *							
ESKOM DRAWING No. D-DT-6050 *							
SAP MATERIAL No.:		0187187					
SHORT DESCRIPTION:		KEY, PADLOCK, LV MASTER, KZN OU D6050					
TECH. DESCRIPTION:							
KEY FOR WEATHER PROOF PADLOCK * FOR KWAZULU NATAL OPERATING UNIT ONLY *							
MATERIAL: BRASS * COLOUR: ORANGE * IDENTIFICATION CODE: 2.5mm HIGH *							
ESKOM DRAWING No. D-DT-6050 *							
SAP MATERIAL No.:		0187188					
SHORT DESCRIPTION:		KEY, PADLOCK, LV MASTER, WC OU D6050					
TECH. DESCRIPTION:							
KEY FOR WEATHER PROOF PADLOCK * FOR WESTERN CAPE OPERATING UNIT ONLY *							
MATERIAL: BRASS * COLOUR: ORANGE * IDENTIFICATION CODE: 2.5mm HIGH *							
ESKOM DRAWING No. D-DT-6050 *							
SAP MATERIAL No.:		0573500					
SHORT DESCRIPTION:		KEY:LV MASTER ORG NC OU;STRAIGHT;BRASS					
TECH. DESCRIPTION:							
KEY: TYPE: LV MASTER ORG NC OU; STYLE: STRAIGHT;							
MATERIAL: BRASS; FOR WEATHER PROOF PADLOCK;							
NORTHERN CAPE OPERATING UNIT ONLY;							
COLOUR: ORANGE; IDENTIFICATION CODE: 2.5MM HIGH;							
ESKOM DRAWING No. D-DT-6050 *							
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED		P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013	
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.		VvZ	VvZ	C.D.SMITH	12/08/2004	
1	ALL PADLOCKS REPLACED AND KEYS ADDED		VvZ	VvZ	C.D.SMITH	6/5/02	
REV	REVISION DESCRIPTION		BY	CHKD	AUTH	DATE	REF. DRAWINGS
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE		SAP No:	
				NTS		0187186	
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:		0187187	
				SERIES 6000		0573500	
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:		SET	SHEET
				6050		45	34
				D-DT-6050			3

SPEC SHEET

SAP MATERIAL No.:		0187189					
SHORT DESCRIPTION:		KEY, PADLOCK, LV MASTER, EC OU D6050					
TECH. DESCRIPTION:							
KEY FOR WEATHER PROOF PADLOCK * FOR EASTERN CAPE OPERATING UNIT ONLY *							
MATERIAL: BRASS * COLOUR: ORANGE * IDENTIFICATION CODE: 2.5mm HIGH *							
ESKOM DRAWING No. D-DT-6050 *							
SAP MATERIAL No.:		0187190					
SHORT DESCRIPTION:		KEY, PADLOCK, LV MASTER, L OU D6050					
TECH. DESCRIPTION:							
KEY FOR WEATHER PROOF PADLOCK * FOR LIMPOPO OPERATING UNIT ONLY *							
MATERIAL: BRASS * COLOUR: ORANGE * IDENTIFICATION CODE: 2.5mm HIGH *							
ESKOM DRAWING No. D-DT-6050 *							
SAP MATERIAL No.:		0187191					
SHORT DESCRIPTION:		KEY, PADLOCK, LV MASTER, MP OU D6050					
TECH. DESCRIPTION:							
KEY FOR WEATHER PROOF PADLOCK * FOR MPUMALANGA OPERATING UNIT ONLY *							
MATERIAL: BRASS * COLOUR: ORANGE * IDENTIFICATION CODE: 2.5mm HIGH *							
ESKOM DRAWING No. D-DT-6050 *							
SAP MATERIAL No.:		0187192					
SHORT DESCRIPTION:		KEY, PADLOCK, LV MASTER, FS OU D6050					
TECH. DESCRIPTION:							
KEY FOR WEATHER PROOF PADLOCK * FOR FREE STATE OPERATING UNIT ONLY *							
MATERIAL: BRASS * COLOUR: ORANGE * IDENTIFICATION CODE: 2.5mm HIGH *							
ESKOM DRAWING No. D-DT-6050 *							
SAP MATERIAL No.:		0573723					
SHORT DESCRIPTION:		KEY:LV MASTER ORG NW OU;STRAIGHT;BRASS					
TECH. DESCRIPTION:							
KEY FOR WEATHER PROOF PADLOCK * FOR NORTH-WEST OPERATING UNIT ONLY *							
MATERIAL: BRASS * COLOUR: ORANGE * IDENTIFICATION CODE: 2.5mm HIGH *							
ESKOM DRAWING No. D-DT-6050 *							
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED		P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013	
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.		VvZ	VvZ	C.D.SMITH	12/08/2004	
1	ALL PADLOCKS REPLACED AND KEYS ADDED		VvZ	VvZ	C.D.SMITH	6/5/02	
REV	REVISION DESCRIPTION		BY	CHKD	AUTH	DATE	REF. DRAWINGS
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE NTS		SAP No:	
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:		0187189 0187191	
				SERIES 6000		0187192 0573723	
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No: 6050		SET	SHEET
				D-DT-6050		45	35
							REV
							3

SPEC SHEET

SAP MATERIAL No.:		0187193					
SHORT DESCRIPTION:		KEY, PADLOCK, PROH MASTER, G OU D6050					
TECH. DESCRIPTION:							
KEY FOR WEATHER PROOF PADLOCK * FOR GAUTENG OPERATING UNIT ONLY *							
MATERIAL: BRASS * COLOUR: GREEN * IDENTIFICATION CODE: 2.5mm HIGH *							
ESKOM DRAWING No. D-DT-6050 *							
SAP MATERIAL No.:		0187194					
SHORT DESCRIPTION:		KEY, PADLOCK, PROH MASTER, KZN OU D6050					
TECH. DESCRIPTION:							
KEY FOR WEATHER PROOF PADLOCK * FOR KWAZULU NATAL OPERATING UNIT ONLY *							
MATERIAL: BRASS * COLOUR: GREEN * IDENTIFICATION CODE: 2.5mm HIGH *							
ESKOM DRAWING No. D-DT-6050 *							
SAP MATERIAL No.:		0187195					
SHORT DESCRIPTION:		KEY, PADLOCK, PROH MASTER, WC OU D6050					
TECH. DESCRIPTION:							
KEY FOR WEATHER PROOF PADLOCK * FOR WESTERN CAPE OPERATING UNIT ONLY *							
MATERIAL: BRASS * COLOUR: GREEN * IDENTIFICATION CODE: 2.5mm HIGH *							
ESKOM DRAWING No. D-DT-6050 *							
SAP MATERIAL No.:		0573501					
SHORT DESCRIPTION:		KEY:PROH MASTER GRN NC OU;STRAIGHT					
TECH. DESCRIPTION:							
KEY: TYPE: PROH MASTER GRN NC OU; STYLE: STRAIGHT;							
MATERIAL: BRASS; FOR WEATHER PROOF PADLOCK;							
NORTHERN CAPE OPERATING UNIT ONLY;							
COLOUR: GREEN; IDENTIFICATION CODE: 2.5MM HIGH;							
ESKOM DRAWING No. D-DT-6050 *							
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED		P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013	
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.		VvZ	VvZ	C.D.SMITH	12/08/2004	
1	ALL PADLOCKS REPLACED AND KEYS ADDED		VvZ	VvZ	C.D.SMITH	6/5/02	
REV	REVISION DESCRIPTION		BY	CHKD	AUTH	DATE	REF. DRAWINGS
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE		SAP No:	
				NTS		0187193	
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:		0187194	
				SERIES 6000		0573501	
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:		SET	SHEET
				6050		45	36
						REV	3

SPEC SHEET

SAP MATERIAL No.:	0187196
SHORT DESCRIPTION:	KEY, PADLOCK, PROH MASTER, EC OU D6050
TECH. DESCRIPTION:	
KEY FOR WEATHER PROOF PADLOCK * FOR EASTERN CAPE OPERATING UNIT ONLY *	
MATERIAL: BRASS * COLOUR: GREEN * IDENTIFICATION CODE: 2.5mm HIGH *	
ESKOM DRAWING No. D-DT-6050 *	


SAP MATERIAL No.:	0187197
SHORT DESCRIPTION:	KEY, PADLOCK, PROH MASTER, L OU D6050
TECH. DESCRIPTION:	
KEY FOR WEATHER PROOF PADLOCK * FOR LIMPOPO OPERATING UNIT ONLY *	
MATERIAL: BRASS * COLOUR: GREEN * IDENTIFICATION CODE: 2.5mm HIGH *	
ESKOM DRAWING No. D-DT-6050 *	

SAP MATERIAL No.:	0187198
SHORT DESCRIPTION:	KEY, PADLOCK, PROH MASTER, MP OU D6050
TECH. DESCRIPTION:	
KEY FOR WEATHER PROOF PADLOCK * FOR MPUMALANGA OPERATING UNIT ONLY *	
MATERIAL: BRASS * COLOUR: GREEN * IDENTIFICATION CODE: 2.5mm HIGH *	
ESKOM DRAWING No. D-DT-6050 *	

SAP MATERIAL No.:	0187199
SHORT DESCRIPTION:	KEY, PADLOCK, PROH MASTER, FS OU D6050
TECH. DESCRIPTION:	
KEY FOR WEATHER PROOF PADLOCK * FOR FREE STATE OPERATING UNIT ONLY *	
MATERIAL: BRASS * COLOUR: GREEN * IDENTIFICATION CODE: 2.5mm HIGH *	
ESKOM DRAWING No. D-DT-6050 *	

SAP MATERIAL No.:	0573724
SHORT DESCRIPTION:	KEY:PROH MASTER GRN NW OU;STRAIGHT
TECH. DESCRIPTION:	
KEY FOR WEATHER PROOF PADLOCK * FOR NORTH-WEST OPERATING UNIT ONLY *	
MATERIAL: BRASS * COLOUR: GREEN * IDENTIFICATION CODE: 2.5mm HIGH *	
ESKOM DRAWING No. D-DT-6050 *	


3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED	P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013	
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.	VvZ	VvZ	C.D.SMITH	12/08/2004	
1	ALL PADLOCKS REPLACED AND KEYS ADDED	VvZ	VvZ	C.D.SMITH	6/5/02	
REV	REVISION DESCRIPTION	BY	CHKD	AUTH	DATE	REF. DRAWINGS

AUTH:	PHIL CROWDY	DATE:	03/98	SCALE NTS	 D-DT-6050	SAP No:			
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:		0187196 0187197	0187198 0187199 0573724		
				SERIES 6000					
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No: 6050		SET	SHEET	REV	
					45	37	3		

SPEC SHEET


SAP MATERIAL No.:		0187200	
SHORT DESCRIPTION:		KEY, PADLOCK, OPER MASTER, G OU D6050	
TECH. DESCRIPTION:			
KEY FOR WEATHER PROOF PADLOCK * FOR GAUTENG OPERATING UNIT ONLY *			
MATERIAL: BRASS * COLOUR: YELLOW * IDENTIFICATION CODE: 2.5mm HIGH *			
ESKOM DRAWING No. D-DT-6050 *			
SAP MATERIAL No.:		0187211	
SHORT DESCRIPTION:		KEY, PADLOCK, OPER MASTER, KZN OU D6050	
TECH. DESCRIPTION:			
KEY FOR WEATHER PROOF PADLOCK * FOR KWAZULU NATAL OPERATING UNIT ONLY *			
MATERIAL: BRASS * COLOUR: YELLOW * IDENTIFICATION CODE: 2.5mm HIGH *			
ESKOM DRAWING No. D-DT-6050 *			
SAP MATERIAL No.:		0187212	
SHORT DESCRIPTION:		KEY, PADLOCK, OPER MASTER, WC OU D6050	
TECH. DESCRIPTION:			
KEY FOR WEATHER PROOF PADLOCK * FOR WESTERN CAPE OPERATING UNIT ONLY *			
MATERIAL: BRASS * COLOUR: YELLOW * IDENTIFICATION CODE: 2.5mm HIGH *			
ESKOM DRAWING No. D-DT-6050 *			
SAP MATERIAL No.:		0573502	
SHORT DESCRIPTION:		KEY:OPER MASTER YEL NC OU;STRAIGHT	
TECH. DESCRIPTION:			
KEY: TYPE: OPER MASTER YEL NC OU; STYLE: STRAIGHT;			
MATERIAL: BRASS; FOR WEATHER PROOF PADLOCK;			
NORTHERN CAPE OPERATING UNIT ONLY;			
COLOUR: YELLOW; IDENTIFICATION CODE: 2.5MM HIGH;			
ESKOM DRAWING No. D-DT-6050 *			

3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED		P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013	
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.		VvZ	VvZ	C.D.SMITH	12/08/2004	
1	ALL PADLOCKS REPLACED AND KEYS ADDED		VvZ	VvZ	C.D.SMITH	6/5/02	
REV	REVISION DESCRIPTION		BY	CHKD	AUTH	DATE	REF. DRAWINGS
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE		SAP No:	
				NTS		0187200	
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:		0187211	
				SERIES 6000		0573502	
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:		SET	SHEET
				6050		45	38
						REV	3




D-DT-6050

SPEC SHEET

SAP MATERIAL No.:		0187213					
SHORT DESCRIPTION:		KEY, PADLOCK, OPER MASTER, EC OU D6050					
TECH. DESCRIPTION:							
KEY FOR WEATHER PROOF PADLOCK * FOR EASTERN CAPE OPERATING UNIT ONLY *							
MATERIAL: BRASS * COLOUR: YELLOW * IDENTIFICATION CODE: 2.5mm HIGH *							
ESKOM DRAWING No. D-DT-6050 *							
SAP MATERIAL No.:		0187214					
SHORT DESCRIPTION:		KEY, PADLOCK, OPER MASTER, L OU D6050					
TECH. DESCRIPTION:							
KEY FOR WEATHER PROOF PADLOCK * FOR LIMPOPO OPERATING UNIT ONLY *							
MATERIAL: BRASS * COLOUR: YELLOW * IDENTIFICATION CODE: 2.5mm HIGH *							
ESKOM DRAWING No. D-DT-6050 *							
SAP MATERIAL No.:		0187215					
SHORT DESCRIPTION:		KEY, PADLOCK, OPER MASTER, MP OU D6050					
TECH. DESCRIPTION:							
KEY FOR WEATHER PROOF PADLOCK * FOR MPUMALANGA OPERATING UNIT ONLY *							
MATERIAL: BRASS * COLOUR: YELLOW * IDENTIFICATION CODE: 2.5mm HIGH *							
ESKOM DRAWING No. D-DT-6050 *							
SAP MATERIAL No.:		0187216					
SHORT DESCRIPTION:		KEY, PADLOCK, OPER MASTER, FS OU D6050					
TECH. DESCRIPTION:							
KEY FOR WEATHER PROOF PADLOCK * FOR FREE STATE OPERATING UNIT ONLY *							
MATERIAL: BRASS * COLOUR: YELLOW * IDENTIFICATION CODE: 2.5mm HIGH *							
ESKOM DRAWING No. D-DT-6050 *							
SAP MATERIAL No.:		0573716					
SHORT DESCRIPTION:		KEY:OPER MASTER YEL NW OU;STRAIGHT					
TECH. DESCRIPTION:							
KEY FOR WEATHER PROOF PADLOCK * FOR NORTH-WEST OPERATING UNIT ONLY *							
MATERIAL: BRASS * COLOUR: YELLOW * IDENTIFICATION CODE: 2.5mm HIGH *							
ESKOM DRAWING No. D-DT-6050 *							
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED		P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013	
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.		VvZ	VvZ	C.D.SMITH	12/08/2004	
1	ALL PADLOCKS REPLACED AND KEYS ADDED		VvZ	VvZ	C.D.SMITH	6/5/02	
REV	REVISION DESCRIPTION		BY	CHKD	AUTH	DATE	REF. DRAWINGS
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE NTS	<div></div> <div>D-DT-6050</div>		
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:			
				SERIES 6000			
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No: 6050			
					SET	SHEET	REV
					45	39	3

SPEC SHEET

SAP MATERIAL No.:		0187217	
SHORT DESCRIPTION:		KEY, PADLOCK, LIVE MASTER, G OU D6050	
TECH. DESCRIPTION:			
KEY FOR WEATHER PROOF PADLOCK * FOR GAUTENG OPERATING UNIT ONLY *			
MATERIAL: BRASS * COLOUR: BLACK * IDENTIFICATION CODE: 2.5mm HIGH *			
ESKOM DRAWING No. D-DT-6050 *			
SAP MATERIAL No.:		0187218	
SHORT DESCRIPTION:		KEY, PADLOCK, LIVE MASTER, KZN OU D6050	
TECH. DESCRIPTION:			
KEY FOR WEATHER PROOF PADLOCK * FOR KWAZULU NATAL OPERATING UNIT ONLY *			
MATERIAL: BRASS * COLOUR: BLACK * IDENTIFICATION CODE: 2.5mm HIGH *			
ESKOM DRAWING No. D-DT-6050 *			
SAP MATERIAL No.:		0187219	
SHORT DESCRIPTION:		KEY, PADLOCK, LIVE MASTER, WC OU D6050	
TECH. DESCRIPTION:			
KEY FOR WEATHER PROOF PADLOCK * FOR WESTERN CAPE OPERATING UNIT ONLY *			
MATERIAL: BRASS * COLOUR: BLACK * IDENTIFICATION CODE: 2.5mm HIGH *			
ESKOM DRAWING No. D-DT-6050 *			
SAP MATERIAL No.:		0573503	
SHORT DESCRIPTION:		KEY:LIVE MASTER BLK NC OU;STRAIGHT	
TECH. DESCRIPTION:			
KEY: TYPE: LIVE MASTER BLK NC OU; STYLE: STRAIGHT;			
MATERIAL: BRASS; FOR WEATHER PROOF PADLOCK;			
NORTHERN CAPE OPERATING UNIT ONLY;			
COLOUR: BLACK;			
IDENTIFICATION CODE: 2.5MM HIGH;			
ESKOM DRAWING No. D-DT-6050 *			

3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED		P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013		
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.		VvZ	VvZ	C.D.SMITH	12/08/2004		
1	ALL PADLOCKS REPLACED AND KEYS ADDED		VvZ	VvZ	C.D.SMITH	6/5/02		
REV	REVISION DESCRIPTION		BY	CHKD	AUTH	DATE	REF. DRAWINGS	
AUTH:	PHIL CROWDY	DATE:	03/98	 D-DT-6050		SAP No:		0187219 0573503
CHKD:	C.B. CLARK	DATE:	03/98			0187217		
						0187218		
						SET	SHEET	REV
DRAWN:	J.F.SCHOLTZ	DATE:	02/98			45	40	3

SPEC SHEET

SAP MATERIAL No.:	0187220
SHORT DESCRIPTION:	KEY, PADLOCK, LIVE MASTER, EC OU D6050
TECH. DESCRIPTION:	
KEY FOR WEATHER PROOF PADLOCK * FOR EASTERN CAPE OPERATING UNIT ONLY *	
MATERIAL: BRASS * COLOUR: BLACK * IDENTIFICATION CODE: 2.5mm HIGH *	
ESKOM DRAWING No. D-DT-6050 *	


SAP MATERIAL No.:	0187221
SHORT DESCRIPTION:	KEY, PADLOCK, LIVE MASTER, L OU D6050
TECH. DESCRIPTION:	
KEY FOR WEATHER PROOF PADLOCK * FOR LIMPOPO OPERATING UNIT ONLY *	
MATERIAL: BRASS * COLOUR: BLACK * IDENTIFICATION CODE: 2.5mm HIGH *	
ESKOM DRAWING No. D-DT-6050 *	

SAP MATERIAL No.:	0187222
SHORT DESCRIPTION:	KEY, PADLOCK, LIVE MASTER, MP OU D6050
TECH. DESCRIPTION:	
KEY FOR WEATHER PROOF PADLOCK * FOR MPUMALANGA OPERATING UNIT ONLY *	
MATERIAL: BRASS * COLOUR: BLACK * IDENTIFICATION CODE: 2.5mm HIGH *	
ESKOM DRAWING No. D-DT-6050 *	


SAP MATERIAL No.:	0187223
SHORT DESCRIPTION:	KEY, PADLOCK, LIVE MASTER, FS OU D6050
TECH. DESCRIPTION:	
KEY FOR WEATHER PROOF PADLOCK * FOR FREE STATE OPERATING UNIT ONLY *	
MATERIAL: BRASS * COLOUR: BLACK * IDENTIFICATION CODE: 2.5mm HIGH *	
ESKOM DRAWING No. D-DT-6050 *	

SAP MATERIAL No.:	0573717
SHORT DESCRIPTION:	KEY:LIVE MASTER BLK NW OU;STRAIGHT
TECH. DESCRIPTION:	
KEY FOR WEATHER PROOF PADLOCK * FOR NORTH-WEST OPERATING UNIT ONLY *	
MATERIAL: BRASS * COLOUR: BLACK * IDENTIFICATION CODE: 2.5mm HIGH *	
ESKOM DRAWING No. D-DT-6050 *	

3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED	P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013	
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.	VvZ	VvZ	C.D.SMITH	12/08/2004	
1	ALL PADLOCKS REPLACED AND KEYS ADDED	VvZ	VvZ	C.D.SMITH	6/5/02	
REV	REVISION DESCRIPTION	BY	CHKD	AUTH	DATE	REF. DRAWINGS

AUTH:	PHIL CROWDY	DATE:	03/98	SCALE NTS	 D-DT-6050	SAP No:	
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:		0187220 0187221	0187222 0187223 0573717
				SERIES 6000		SET	SHEET
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No: 6050		45	41
							REV
							3

SPEC SHEET

SAP MATERIAL No.:		0187226						
SHORT DESCRIPTION:		KEY, PADLOCK, TSO MASTER, G OU D6050						
TECH. DESCRIPTION:								
KEY FOR WEATHER PROOF PADLOCK * FOR GAUTENG OPERATING UNIT ONLY *								
MATERIAL: BRASS * COLOUR: BLUE * IDENTIFICATION CODE: 2.5mm HIGH *								
ESKOM DRAWING No. D-DT-6050 *								
SAP MATERIAL No.:		0187227						
SHORT DESCRIPTION:		KEY, PADLOCK, TSO MASTER, KZN OU D6050						
TECH. DESCRIPTION:								
KEY FOR WEATHER PROOF PADLOCK * FOR KWAZULU NATAL OPERATING UNIT ONLY *								
MATERIAL: BRASS * COLOUR: BLUE * IDENTIFICATION CODE: 2.5mm HIGH *								
ESKOM DRAWING No. D-DT-6050 *								
SAP MATERIAL No.:		0187228						
SHORT DESCRIPTION:		KEY, PADLOCK, TSO MASTER, WC OU D6050						
TECH. DESCRIPTION:								
KEY FOR WEATHER PROOF PADLOCK * FOR WESTERN CAPE OPERATING UNIT ONLY *								
MATERIAL: BRASS * COLOUR: BLUE * IDENTIFICATION CODE: 2.5mm HIGH *								
ESKOM DRAWING No. D-DT-6050 *								
SAP MATERIAL No.:		0573504						
SHORT DESCRIPTION:		KEY:TSO MASTER BLU NC OU;STRAIGHT;BRASS						
TECH. DESCRIPTION:								
KEY: TYPE: TSO MASTER BLU NC OU; STYLE: STRAIGHT;								
MATERIAL: BRASS; FOR WEATHER PROOF PADLOCK;								
NORTHERN CAPE OPERATING UNIT ONLY;								
COLOUR: BLUE; IDENTIFICATION CODE: 2.5MM HIGH;								
ESKOM DRAWING No. D-DT-6050 *								
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED			P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013	
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.			VvZ	VvZ	C.D.SMITH	12/08/2004	
1	ALL PADLOCKS REPLACED AND KEYS ADDED			VvZ	VvZ	C.D.SMITH	6/5/02	
REV	REVISION DESCRIPTION			BY	CHKD	AUTH	DATE	REF. DRAWINGS
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE		<div><div></div><div>D-DT-6050</div></div>		
				NTS				
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:				
				SERIES 6000				
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:				
				6050				
						SET	SHEET	REV
						45	42	3

SPEC SHEET

SAP MATERIAL No.:	0187229
SHORT DESCRIPTION:	KEY, PADLOCK, TSO MASTER, EC OU D6050
TECH. DESCRIPTION:	
KEY FOR WEATHER PROOF PADLOCK * FOR EASTERN CAPE OPERATING UNIT ONLY *	
MATERIAL: BRASS * COLOUR: BLUE * IDENTIFICATION CODE: 2.5mm HIGH *	
ESKOM DRAWING No. D-DT-6050 *	

SAP MATERIAL No.:	0187230
SHORT DESCRIPTION:	KEY, PADLOCK, TSO MASTER, L OU D6050
TECH. DESCRIPTION:	
KEY FOR WEATHER PROOF PADLOCK * FOR LIMPOPO OPERATING UNIT ONLY *	
MATERIAL: BRASS * COLOUR: BLUE * IDENTIFICATION CODE: 2.5mm HIGH *	
ESKOM DRAWING No. D-DT-6050 *	

SAP MATERIAL No.:	0187231
SHORT DESCRIPTION:	KEY, PADLOCK, TSO MASTER, MP OU D6050
TECH. DESCRIPTION:	
KEY FOR WEATHER PROOF PADLOCK * FOR MPUMALANGA OPERATING UNIT ONLY *	
MATERIAL: BRASS * COLOUR: BLUE * IDENTIFICATION CODE: 2.5mm HIGH *	
ESKOM DRAWING No. D-DT-6050 *	

SAP MATERIAL No.:	0187232
SHORT DESCRIPTION:	KEY, PADLOCK, TSO MASTER, FS OU D6050
TECH. DESCRIPTION:	
KEY FOR WEATHER PROOF PADLOCK * FOR FREE STATE OPERATING UNIT ONLY *	
MATERIAL: BRASS * COLOUR: BLUE * IDENTIFICATION CODE: 2.5mm HIGH *	
ESKOM DRAWING No. D-DT-6050 *	


SAP MATERIAL No.:	0573718
SHORT DESCRIPTION:	KEY:TSO MASTER BLU NW OU;STRAIGHT;BRASS
TECH. DESCRIPTION:	
KEY FOR WEATHER PROOF PADLOCK * FOR NORTH-WESTERN OPERATING UNIT ONLY *	
MATERIAL: BRASS * COLOUR: BLUE * IDENTIFICATION CODE: 2.5mm HIGH *	
ESKOM DRAWING No. D-DT-6050 *	

3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED	P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013				
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.	VvZ	VvZ	C.D.SMITH	12/08/2004				
1	ALL PADLOCKS REPLACED AND KEYS ADDED	VvZ	VvZ	C.D.SMITH	6/5/02				
REV	REVISION DESCRIPTION	BY	CHKD	AUTH	DATE	REF. DRAWINGS			
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE NTS	SAP No: 0187229 0187230				
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:			0187231 0187232 0573718		
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	SERIES 6000	D-DT-6050		SET	SHEET	REV
				FILE No:			45	43	3
				6050					

SPEC SHEET

SAP MATERIAL No.:		0573505					
SHORT DESCRIPTION:		KEY:GEN MASTER WHT G OU;STRAIGHT;BRASS					
TECH. DESCRIPTION:							
KEY: TYPE: GEN MASTER WHT G OU; STYLE: STRAIGHT; MATERIAL: BRASS; FOR WEATHER PROOF PADLOCK; GAUTENG OPERATING UNIT ONLY; COLOUR: WHITE; IDENTIFICATION CODE: 2.5MM HIGH; ESKOM DRAWING No. D-DT-6050 *							
SAP MATERIAL No.:		0573506					
SHORT DESCRIPTION:		KEY:GEN MASTER WHT KZN OU;STRAIGHT					
TECH. DESCRIPTION:							
KEY: TYPE: GEN MASTER WHT KZN OU; STYLE: STRAIGHT; MATERIAL: BRASS; FOR WEATHER PROOF PADLOCK; KWAZULU NATAL OPERATING UNIT ONLY; COLOUR: WHITE; IDENTIFICATION CODE: 2.5MM HIGH; ESKOM DRAWING No. D-DT-6050 *							
SAP MATERIAL No.:		0573507					
SHORT DESCRIPTION:		KEY:GEN MASTER WHT WC OU;STRAIGHT;BRASS					
TECH. DESCRIPTION:							
KEY: TYPE: GEN MASTER WHT WC OU; STYLE: STRAIGHT; MATERIAL: BRASS; FOR WEATHER PROOF PADLOCK; WESTERN CAPE OPERATING UNIT ONLY; COLOUR: WHITE; IDENTIFICATION CODE: 2.5MM HIGH; ESKOM DRAWING No. D-DT-6050 *							
SAP MATERIAL No.:		0573508					
SHORT DESCRIPTION:		KEY:GEN MASTER WHT NC OU;STRAIGHT;BRASS					
TECH. DESCRIPTION:							
KEY: TYPE: GEN MASTER WHT NC OU; STYLE: STRAIGHT; MATERIAL: BRASS; FOR WEATHER PROOF PADLOCK; NORTHERN CAPE OPERATING UNIT ONLY; COLOUR: WHITE; IDENTIFICATION CODE: 2.5MM HIGH; ESKOM DRAWING No. D-DT-6050 *							
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED		P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013	
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.		VvZ	VvZ	C.D.SMITH	12/08/2004	
1	ALL PADLOCKS REPLACED AND KEYS ADDED		VvZ	VvZ	C.D.SMITH	6/5/02	
REV	REVISION DESCRIPTION		BY	CHKD	AUTH	DATE	REF. DRAWINGS
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE		SAP No:	
				NTS		0573505	
CHKD:	C.B. CLARK	DATE:	03/98	CAD REF:		0573507	
				SERIES 6000		0573506	
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:		SET	SHEET
				6050		45	44
						REV	3

SPEC SHEET

SAP MATERIAL No.:		0573509								
SHORT DESCRIPTION:		KEY:GEN MASTER WHT EC OU;STRAIGHT;BRASS								
TECH. DESCRIPTION:										
KEY: TYPE: GEN MASTER WHT EC OU; STYLE: STRAIGHT; MATERIAL: BRASS; FOR WEATHER PROOF PADLOCK; EASTERN CAPE OPERATING UNIT ONLY; COLOUR: WHITE; IDENTIFICATION CODE: 2.5MM HIGH; ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0573510								
SHORT DESCRIPTION:		KEY:GEN MASTER WHT L OU;STRAIGHT;BRASS								
TECH. DESCRIPTION:										
KEY: TYPE: GEN MASTER WHT L OU; STYLE: STRAIGHT; MATERIAL: BRASS; FOR WEATHER PROOF PADLOCK; LIMPOPO OPERATING UNIT ONLY; COLOUR: WHITE; IDENTIFICATION CODE: 2.5MM HIGH; ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0573511								
SHORT DESCRIPTION:		KEY:GEN MASTER WHT MP OU;STRAIGHT;BRASS								
TECH. DESCRIPTION:										
KEY: TYPE: GEN MASTER WHT MP OU; STYLE: STRAIGHT; MATERIAL: BRASS; FOR WEATHER PROOF PADLOCK; MPUMALANGA OPERATING UNIT ONLY; COLOUR: WHITE; IDENTIFICATION CODE: 2.5MM HIGH; ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0573513								
SHORT DESCRIPTION:		KEY:GEN MASTER WHT FS OU;STRAIGHT;BRASS								
TECH. DESCRIPTION:										
KEY: TYPE: GEN MASTER WHT FS OU; STYLE: STRAIGHT; MATERIAL: BRASS; FOR WEATHER PROOF PADLOCK; NORTH WESTERN OPERATING UNIT ONLY; COLOUR: WHITE; IDENTIFICATION CODE: 2.5MM HIGH; ESKOM DRAWING No. D-DT-6050 *										
SAP MATERIAL No.:		0573512								
SHORT DESCRIPTION:		KEY:GEN MASTER WHT NW OU;STRAIGHT;BRASS								
TECH. DESCRIPTION:										
KEY: TYPE: GEN MASTER WHT NW OU; STYLE: STRAIGHT; MATERIAL: BRASS; FOR WEATHER PROOF PADLOCK; FREE STATE OPERATING UNIT ONLY; COLOUR: WHITE; IDENTIFICATION CODE: 2.5MM HIGH; ESKOM DRAWING No. D-DT-6050 *										
3	ALL OPTIONS ADDED FOR NORTHERN CAPE AND WHITE WEATHER PROOF PADLOCKS ADDED				P.A.T.	D. NTOMBELA	C.D.SMITH	11/09/2013		
2	LOGO IN TITLE BLOCK CHANGED AS PER CORPORATE IDENTITY. SFD's AND LONG TEXT DESCRIPTIONS UPDATED.				VvZ	VvZ	C.D.SMITH	12/08/2004		
1	ALL PADLOCKS REPLACED AND KEYS ADDED				VvZ	VvZ	C.D.SMITH	6/5/02		
REV	REVISION DESCRIPTION				BY	CHKD	AUTH	DATE	REF. DRAWINGS	
AUTH:	PHIL CROWDY	DATE:	03/98	SCALE	 D-DT-6050			SAP No:		
CHKD:	C.B. CLARK	DATE:	03/98	NTS				0573509		0573513 0573512
				CAD REF:				0573510		
				SERIES 6000				0573511		
DRAWN:	J.F.SCHOLTZ	DATE:	02/98	FILE No:				SET	SHEET	REV
				6050				45	45	3