

Returnable: Annexure A – Schedule of Compliance (General Tools)						
	Description and Specification	Schedule A (Returnable by Tender(s)	Photo/Picture(s) Yes/No	Datasheet Yes/No	Certificate(s) Yes/No	Eskom Evaluation (COMPLIANT or NON-COMPLIANT)
1	Cordless Impact Wrench: Applicable battery-18v Li-ion, 1500mAh (XB-1500)/ 3000mAh (XB-3000) No load speed:0-2.200min-1. Impact rate:0-3,000-1. Max torque: 310Nm.	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
2	Binoculars (10x50): 10x50 SP S-Series WP Binocular, Fully Multicoated Optics, Slip-Resistant Rubberized Armouring, Water & Fog Proof.	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
3	Grinder, Battery Operated 115mm with 2x3 AH batteries a7 Charger: Voltage: 100-240V ~/50-60Hz. Battery Amps: 4.0Ah. Rated power: 18V No load. Speed: 0-7,500/min. Disc diameter: 115mm.	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
4	LN Keys Socket Set: SOCKET, WRENCH SET: TYPE: PROFESSIONAL; MATERIAL: HARDENED STEEL; SIZE RANGE: 2-10 MM; SPECIAL FEATURES: METRIC, ALLEN KEYS FULL SET	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
5	Hydraulic Hand Conductor Cutter: CUTTER, CABLE: TYPE: CONDUCTOR; CABLE SIZE ACCOMMODATED: 55 MM; COMMERCIAL SIZE: 595 MM; HANDLE MATE WITH A CARRY BAG	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
6	ACSR Cable Stripper (including dies): STRIPPER: TYPE: ALUMINUM CABLE STRANDS; RANGE: 23-43 MM; SPECIFICATION: CUTS ALUMINUM CONDUCTOR STRANDS.	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
7	Inverter 2000W pure sign wave: INVERTER: TYPE: RCD PROTECTED; POWER: 2 KW; OUTPUT RATING: 230VAC 10A 50HZ; INPUT RATING: 12/24 V	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
8	Dinosaur Coma Long: Load rating of 7-80KN, Weight 1,0-18 Kg with sag adjusting and tensioning on a overhead line construction. Material-aluminium alloy. (wire grip clamp. Come along clamp) for dinosaur conductor.	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
9	Generator (6.5KVA): Powerfull 13hp petrol engine. Low oil engine shutdown protection. Automatic Voltage regulator (AVR) for sensitive electronic equipment 2x3 pin south african plugs with circuit breaker. Includes wheel kit and electric start with battery. Low noise 84dB.	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
10	GPS Nuvi 2589 LMT: Display type: TFT, Screen size: 5, Screen resolution:480, 272, Interface type: Tochsreen.	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
11	Rope Grabber 16mm: CLAMP, WIRE ROPE: TYPE: SINGLE GRIP, DOUBLE SADDLE; ROPE SIZE: 16 MM; CLAMP MATERIAL: STL; 15T CRANE	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
12	Tool Boxes With Loose Tools:x18 Sockets-8, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 24, 27, 30, 32mm x 1 Universal Joint-1.27cm x 1 Extension Bar- 125mm x 1H handle - 1.27cm x 1 Ratchet- 1.27cm x 4 Slotted Screwdrivers- SL 3.2 X 75mm, 4 x 100mm, 4 x 100mm, 6 x 100mm, 8 x 150mm x 3 phillips screwdrivers - PH 1 x 75mm, PH 2 x 10mm, PH 3 x 150mm x 12 spanner-8, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 22mm x 1 Water pump - 25.4cm x 1 Vice Grip - 25.4 cm x 1 Tape - 5m x 0.019m x 1 Sliding T-Bar- 1.27cm x 1 combination Plier - 180mm x 16.21mm x 1 Trimming Knife x 5 Blades x 1 Toolbox x 9 Allen Key Set - 1.5, 2, 2.5, 3, 4, 5, 6, 8, 10mm x 9 Torx Key Set - T10, 15, 20, 25, 27, 30, 40, 45, 50 x 10 Drill Bits- SL3, 4, 5, PZ1, PZ2, PH1, PH2, PH3, T10, T15.	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
13	Inverter 2000W pure sign wave: TYPE: RCD PROTECTED; POWER: 2 KW; OUTPUT RATING:TYPE: RCD PROTECTED; POWER: 2 KW; OUTPUT RATING:TYPE: RCD PROTECTED; POWER: 2 KW; OUTPUT RATING: 230VAC 10A 50HZ; INPUT RATING: 24/36/48 VDC; ENCLOSURE: STEEL BOX; APPLICATION: ELECTRICAL ROPE TESTER; SPECIFICATION: PURE SINE WAVE; INVERTER 2000W PURE SINE WAVE, MAX INPUT AMPS: 100/66/50, STANDBY POWER: 25W, PEAK EFFICIENCY: 94 PCT	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
14	Bypass Jumpers: TYPE: EARTING SUBST; CONDUCTOR SIZE: 40 MM2; OVERALL LENGTH: 30 MM; MANUF P/N: E-CES/8	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
15	Fox to Bull Comalong: Load rating of 7-80KN, Weight 1.0-18kg with sag adjusting and tensioning on overhead line construction. Material- aluminium alloy. (wire grip clamp. come along clamp	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
16	Bolt Cutter (900mm Heavy duty): Dimnsion, (L) 900mm;Length, 900mm;Material, Alloy; Packaging Types; Each; Product Range, Bolt Cutters.	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
17	RADIO: TYPE: AIR BAND; BANDWIDTH: VHR; POWER SUPPLY: 7.2 VDC(BP-288),11 VDC(EXTERNAL); DIMENSIONS: WD 58.9 X LG 148.4 X THK 31.8 MM; SPECIAL FEATURES: DUST AND WATER PROOF; SPECIFICATION: FCC PART87; STANDARD: MIL-STD-810-C, D, E AND F; AIR BAND TRANSCEIVER	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
18	Jumper 40mm yellx2m shunt LV universal screw on clamp & earth retic: SHUNT: TYPE: CABLE CONDUCTOR; RATING: 40KA; MATERIAL: COPPER; YELLOW 2 METER: WITH UNIVERSAL SCREW CLAMPS ON BOTH ENDS, MARKED WITH MANUFACTURES TRADE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
19	Static Ground (Earth Shunt): CABLE ASSEMBLY: TYPE: EARTH SHUNT; DIAMETER: 40 MM; LENGTH: 2 M; MATERIAL: COPPER; OEM P/N: E-J40Y2-5/51; YELLOW; LV SCREW ON CLAMP STICK HANDLE ONE END EARTH CLAMP OTHER END; INSPECTED PRIOR TO USED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
20	Earth Stick Applicator: CLAMP: TYPE: STICK HEAD; MATERIAL: ALUMINUM; MANUF P/N: M445529B; 6 INCH LONG; WITH EYE SCREW GROUNDING CLAMPS; 6 HEAD (STG no:0722106)	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
21	Air-Compressor: COMPRESSOR, AIR: CAPACITY: 12800 BTU; POTENTIAL: 220 VAC; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE)	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				