


NOTE 1 :

A TRANSITION SLAB 200mm THICK IS REQUIRED TO MATCH LEVEL OF GATE SLAB AND TERRACE CONCRETE ROAD

NOTE :

- (A) = 4m SLIDING GATE FOR SECURITY AND 7,5m SLIDING GATE FOR NON-LETHAL MOTORISED AND FOR DAILY USE.
- (B) = 3m SLIDING GATE FOR SECURITY TO BE OPENED MANUALLY AND POST REMOVED FOR ACCESS OF ABNORMAL VEHICLES ON A ADHOC BASIS.
- (C) = CONCRETE WALL AND SECURITY FENCE TO HAVE SINGLE VEE FOR SECTION NEXT TO SLIDING GATE AS PER DETAIL ON DRG 0.54/5633 SHT. 7 AND 5846

5	TRANSITION CONC. SLAB & NOTE 1 ADDED	PHD	DBN	DJC.S	28.02.13
4	NOTE C ADD. & INSIDE SLIDING GATE SWOPPED TO HAVE BIGGER OPENING - LEFT	PHD	DJC.S	DJC.S	07.11.12
3	ADD 2 x 160 KABELFLEX SLEEVE PIPES	C.F	D.S	DJC.S	14.06.12
2	GENERAL REVISION	PHD	DJC.S	DJC.S	02.03.12
1	NEW SHEET NUMBER REVISED	PHD	DBN	DBN	28.11.11
REV	REVISION DESCRIPTION	BY	CHKD	AUTH	DATE

APPROVED BY DJC. SENEKAL	 Eskom Transmission	ESKOM HOLDINGS LIMITED REG NO. 2002/015527/06		
DATE 17/11/2011				
CHECKED BY PAUL DOYLE	SECURITY FENCE THREE TYPES OF SECURITY SLIDING GATES GENERAL ARRANGEMENT			
DATE 17/11/2011				
DRAWN BY PAUL DOYLE	©	0.54/7470		
DATE 17/11/2011				
SCALE 1:50		SHEET NUMBER 1	REVISION 5	