











NOTE :

1.) ALL STEELWORK TO BE GRADE 300WA.
2.) FOR PAINTING AND PROTECTION OF STEELWORK REFER TO ESKOM SPECIFICATIONS.
3.) ALL HOLES TO BE DIA.18 FOR M16 GRADE 4.8 BOLTS U.O.N.
4.) SLIDING DOOR MECHANISM SHALL BE HILLALDAM COBURN STRAIGHTAWAY DOOR GEAR, INSTALLED TO MANUFACTURERS SPECIFICATIONS.

REV	DATE		BY	CHKD BY	AUTH BY	KKS APP	
7.	02 2009	MEMBER CHANGED TO DR2-FRONT ELEV	DBN		DBN		
6.	14 09 2009	SHEETING RAILS & SAG RODS ADDED	DBN	DBN	D.J.S.		
5.	03 11 08	EXTRACTOR FAN SUPPORT ANGLE ADDED	DBN				
4.	03 10 08	MEMBER NAMES CHANGED	M.M		D.J.S.		
3.	18 11 07	BRICK WALLS RAISED - DOOR ON INSIDE	A.D	D.N.	D.N.		
2.	18 07 06	DR1 ADDED & DOOR REVISED.	A.D	D.P.	D.S.		
1.	18 07 04	SR1/NOTES ADDED.	A.D	D.N.	D.S.		
00	0	FIRST ISSUE					DETAILS
D.O.	REV	■■ REVISION ■■	REV BY	CHKD BY	AUTH BY	KKS APP	0.54/ REFERENCE DRAWINGS
		INDEX REFERENCE :					

ESKOM

SUBSTATION.
WORKSHOPS AND STORES.
GENERAL ARRANGEMENT OF WORKSHOPS AND STORES.

DRG REGISTR			
KKS APP			
AUTH BY			
CHKD BY			
DRAWN BY	03 08 06	APPROVED BY :	APPROVED BY :
SCALE			

0.54/5588 SHEET 1 — REV 7

SIZE GROOTTE A1L